


RHD Non return valve

EO 24° cone end / EO 24° cone end



Series	D1 	DN	L1	L2	L3	S1	S2	S3	Weight g/1 piece	Order code*	PN (bar) ¹⁾		
											CF	A3C	71
L ³⁾	06	3.5	43	29.0	58.0	17	17	14	46	RHD06LOMD	400	250	250
	08	5.5	44	30.0	59.0	19	19	17	61	RHD08LOMD	400	250	250
	10	7.5	54.5	40.5	69.5	22	24	19	104	RHD10LOMD	400	250	250
	12	9.5	57.5	43.5	72.5	27	30	22	166	RHD12LOMD	400	250	250
	15	11.5	61.5	47.5	77.5	27	32	27	192	RHD15LOMD	400	250	250
	18	14.0	66.5	51.5	83.5	36	36	32	292	RHD18LOMD	400	160	160
	22	18.0	76.5	61.5	93.5	41	46	36	472	RHD22LOMD	250	160	160
	28	23.0	84.5	69.5	102.5	50	55	41	746	RHD28LOMD	250	100	100
	35	29.0	95.5	74.5	117.5	60	60	50	1062	RHD35LOMD	250	100	100
	42	29.0	96	74.0	119.0	65	70	60	1518	RHD42LOMD	250	100	100
S ⁴⁾	06	3.5	48.5	34.5	63.5	19	19	17	70	RHD06SOMD	420	400	400
	08	3.5	48.5	34.5	63.5	19	19	19	74	RHD08SOMD	420	400	400
	10	5.5	55.5	40.5	72.5	22	24	22	121	RHD10SOMD	420	400	400
	12	7.5	57.5	42.5	74.5	24	27	24	148	RHD12SOMD	420	400	400
	14	9.5	63.5	47.5	82.5	27	32	27	218	RHD14SOMD	420	315	315
	16	11.5	67.5	50.5	86.5	32	36	30	286	RHD16SOMD	420	315	315
	20	15.0	75.5	54.5	97.5	41	46	36	506	RHD20SOMD	420	250	250
	25	19.0	82.5	58.5	106.5	46	50	46	639	RHD25SOMD	420	250	250
	30	24.0	96.5	69.5	122.5	60	60	50	1157	RHD30SOMD	250	250	250
	38	29.0	107.5	75.5	136.5	65	70	60	1650	RHD38SOMD	250	250	250

¹⁾ Pressure shown = item deliverable

³⁾ L = light series; ⁴⁾ S = heavy series

$\frac{PN \text{ (bar)}}{10} = PN \text{ (MPa)}$

Delivery without nut and ring. Information on ordering complete fittings or alternative sealing materials see page 17.

*Please add the **suffixes** below according to the material/ surface required.

Order code suffixes			
Material	Suffix surface and material	Example	Standard sealing material (no additional suffix needed)
Steel, zinc plated., chrome ⁶⁾ -free	CF	RHD06LOMDCF	NBR
Steel, zinc yellow plated	A3C	RHD06LOMDA3C	NBR
Stainless steel	71	RHD06LOMD71	VIT