



## High-Duty

Reduce standing fatigue at larger or oily workstations



- A very comfortable alternative to cold hard floors.
- Open holes capture spilt liquids and swarf.
- Manufactured from a blend of rubber for better than average resistance to oil and chemicals.
- Available in standard mats, edged on all sides, or as interlocking modules for larger areas.
- Raised circular surface gives excellent underfoot grip.
- Slip tested to DIN 51130.



## Parts

Part Number	Size	Colour	Weight
HI010001	0.9 m x 1.5 m	Black	8.90 kg
HI010002	0.9 m x 1.5 m	Black	9.00 kg
HI010003	0.9 m x 1.5 m	Black	9.00 kg
HI010004	0.9 m x 1.5 m	Black	9.00 kg
HI010005	0.9 m x 1.5 m	Black	9.00 kg

## Technical Specification

Material	Natural rubber/25% NBR compound
Surface Finish	Circular pattern construction for extra grip and holes to allow drainage
Product Height	12 mm
Product Weight	9.2kg
Operating Temperature	< +70°C
Resistance to Chemicals	Limited resistance to chemicals
Environmental Resistance	Suitable for wet and dry environments
UV Resistance	Moderate
Typical Applications	General industrial, Bars, Catering environments, Machine tool areas where swarf is prevalent
Installation Method	Loose lay interlocking mats
Cleaning Method	For regular maintenance, hose with water. For excessive dirt scrub with a mild detergent and rinse.
Country of Origin	India

## Technical Specification

<b>Tensile Strength</b>	ASTM D412, 3 (+/-1)Nm/mm <sup>2</sup>
<b>Elongation</b>	ASTM D412, 200% (+/-50%)
<b>Application Temperature</b>	18°C to 65.5°C
<b>Slip Tested to</b>	DIN 51130 - R10
<b>Manufacturing process</b>	Rubber moulding

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)116 240 1088 or email [sales@cobaeurope.com](mailto:sales@cobaeurope.com)