

# Plate Cylinder: Double Acting, Single Rod Series *MU* ø25, ø32, ø40, ø50, ø63

## How to Order

**MU B 25 □ - 30 D M Z**

**With auto switch** **MDU B 25 □ - 30 D M Z - M9BW S**

• **With auto switch**  
(Built-in magnet)

• **Mounting**

B	Basic
L	Foot
F	Rod flange
G	Head flange
C	Single clevis
D	Double clevis

\* Brackets are shipped together, (but not assembled).

• **Size**

25	Equiv. ø25 piston area
32	Equiv. ø32 piston area
40	Equiv. ø40 piston area
50	Equiv. ø50 piston area
63	Equiv. ø63 piston area

• **Port thread type**

Nil	M thread	ø25
	Rc	
TN	NPT	ø32, ø40
TF	G	ø50, ø63

• **Number of auto switches**

Nil	2 pcs.
S	1 pc.
n	"n" pcs.

• **Auto switch**

Nil	Without auto switch
-----	---------------------

\* Refer to the below table for applicable auto switch models.

• **Rod end configuration**

Nil	Rod end female thread
M	Rod end male thread

• **Action**

D	Double acting
---	---------------

• **Cylinder stroke (mm)**  
Refer to "Standard Stroke" on page 2.

• **Built-in Magnet Cylinder Model**  
If a built-in magnet cylinder without an auto switch is required, there is no need to enter the symbol for the auto switch.  
(Example) MDUL32-30DZ

## Applicable Auto Switches/Refer to Best Pneumatics No. 2 for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model		Lead wire length (m)				Pre-wired connector	Applicable load		
					DC		AC	Perpendicular	In-line	0.5 (Nil)	1 (M)	3 (L)		5 (Z)		
Solid state auto switch	—	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	—	M9NV	M9N	●	●	●	○	○	IC circuit	Relay, PLC
	3-wire (PNP)			12 V		M9PV		M9P	●	●	●	○	○			
	2-wire					M9BV		M9B	●	●	●	○	○			
	3-wire (NPN)			5 V, 12 V		M9NWV		M9NW	●	●	●	○	○	IC circuit		
	3-wire (PNP)			12 V	M9PWV	M9PW		●	●	●	○	○	—			
	2-wire			5 V, 12 V	M9BWV	M9BW		●	●	●	○	○		IC circuit		
	3-wire (NPN)			12 V	M9NAV**	M9NA**		○	○	●	○	○				
	3-wire (PNP)				M9PAV**	M9PA**		○	○	●	○	○				
	2-wire				M9BAV**	M9BA**		○	○	●	○	○	—			
	2-wire (Non-polar)				—	—		P3DW <sup>Note 2)</sup>	●	—	●	●		○		
Reed auto switch	—	Grommet	Yes	3-wire (NPN equivalent)	—	5 V	—	A96V	A96	●	—	●	—	—	IC circuit	—
	None			24 V	12 V	100 V	A93V	A93	●	—	●	—	—	—	—	Relay, PLC
			100 V or less			A90V	A90	●	—	●	—	—	—			

\*\* Water resistant type auto switches can be mounted on the above models, but in such case SMC cannot guarantee water resistance. Consult with SMC regarding water resistant types with the above model numbers.

\* Lead wire length symbols: 0.5 m ..... Nil (Example) M9NW  
1 m ..... M (Example) M9NWM  
3 m ..... L (Example) M9NWL  
5 m ..... Z (Example) M9NWZ

\* Solid state auto switches marked with "○" are produced upon receipt of order.

\* For details about auto switches with pre-wired connector, refer to Best Pneumatics No. 2.

\* Auto switches are shipped together, (but not assembled).

Note 1) The D-M9□V/M9□WV/M9□AV/A9□V auto switches cannot be mounted on the ported surface with some cylinder strokes and sizes of fittings. This should be checked beforehand.

Note 2) The magnetic field resistant auto switch (D-P3DW□) is available only with ø40 to ø63 of the existing MU series. Refer to page 23 for the how-to-order.

## Specifications



Bore size (mm)	25	32	40	50	63
Action	Double acting, Single rod				
Fluid	Air				
Proof pressure	1.05 MPa				
Maximum operating pressure	0.7 MPa				
Minimum operating pressure	0.05 MPa				
Ambient and fluid temperature	-10 to 60°C				
Lubrication	Not required (Non-lube)				
Piston speed	50 to 500 mm/s				
Stroke length tolerance	+1.4 0				
Cushion	Rubber bumper				
Mounting	Foot, Rod flange, Head flange, Single clevis, Double clevis				
Rod end configuration	Rod end male thread, Rod end female thread				
Allowable rotational torque	0.25 N·m		0.55 N·m	1.25 N·m	2.0 N·m
Rod non-rotating accuracy	±1°	±0.8°	±0.5°		

## Standard Stroke

Size	Standard stroke (mm)	Maximum manufacturable stroke (mm)
25, 32, 40 50, 63	5, 10, 15, 20, 25, 30, 35, 40, 45, 50 75, 100, 125, 150, 175, 200, 250, 300	300

- \* Other intermediate strokes can be manufactured upon receipt of order. Please contact SMC.  
 \*\* Strokes longer than 300 mm are not available.

## Mounting Bracket/Part No.

Mounting bracket \ Size	25	32	40	50	63
Foot <sup>Note 1)</sup>	MU-L02	MU-L03	MU-L04	MU-L05	MU-L06
Flange	MU-F02	MU-F03	MU-F04	MU-F05	MU-F06
Single clevis	MU-C02	MU-C03	MU-C04	MU-C05	MU-C06
Double clevis <sup>Note 3)</sup>	MU-D02	MU-D03	MU-D04	MU-D05	MU-D06

- Note 1) When ordering foot bracket, order 2 pieces per cylinder.  
 Note 2) Accessories for each mounting bracket are as follows.  
 Foot/Flange/Single clevis: Body mounting bolt  
 Double clevis: Clevis pin, Type C retaining ring for axis, Body mounting bolt  
 Note 3) Clevis pin and retaining ring are shipped together with double clevis.  
 Note 4) The tightening torque for body mounting bolts is shown in the below table.  
 Note 5) The application of a locking agent (Example: Loctite® 242) to body mounting bolts is recommended.

## Recommended Tightening Torque for Mounting Bracket on Body

Bore size	Thread size	Tightening torque (N·m)
MU25	M5 x 0.8	4.9 to 5.9
MU32	M6 x 1	8.28 to 10.12
MU40	M8 x 1.25	19.8 to 24.2
MU50	M10 x 1.5	39.6 to 48.4
MU63	M12 x 1.75	68.4 to 83.6