

Check-choke valve, Series CC04

- $Q_n 1 \rightarrow 2 = 0.071-1.98 \text{ Cv}$
- direction of throttle $1 \rightarrow 2$
- inlet-side throttling
- push-in fitting / External thread



Working pressure min./max.

8 ... 145 psi

Ambient temperature min./max.


14 ... 140 °F

Medium temperature min./max.

14 ... 140 °F

Medium

Compressed air



Technical data

Part No.	Port 1	Port 2	Throttle bore	Flow	Fig.
			Ø	$Q_n 1 \rightarrow 2$	
R412010581	Ø 4	M5	2 mm	0.071 Cv	Fig. 1
R412010582	Ø 6	M5	2 mm	0.112 Cv	Fig. 1
R412010585	Ø 4	G 1/8	3.5 mm	0.152 Cv	Fig. 2
R412010586	Ø 6	G 1/8	3.5 mm	0.396 Cv	Fig. 2
R412010587	Ø 8	G 1/8	3.5 mm	0.478 Cv	Fig. 2
R412010588	Ø 6	G 1/4	4.5 mm	0.396 Cv	Fig. 3
R412010589	Ø 8	G 1/4	4.5 mm	0.498 Cv	Fig. 3
R412010590	Ø 10	G 1/4	4.5 mm	0.528 Cv	Fig. 3
R412010591	Ø 8	G 3/8	6.6 mm	0.884 Cv	Fig. 4
R412010592	Ø 10	G 3/8	6.6 mm	1.15 Cv	Fig. 4
R412010593	Ø 12	G 3/8	6.6 mm	1.23 Cv	Fig. 4
R412010594	Ø 10	G 1/2	6.6 mm	1.7 Cv	Fig. 5
R412010595	Ø 12	G 1/2	6.6 mm	1.98 Cv	Fig. 5

Nominal flow Q_n at 87 psi and $\Delta p = 14.5 \text{ psi}$

G 1/4: 6.0 Nm -0.6
 G 3/8: 8.0 Nm -1.0
 G 1/2: 10.0 Nm -1.0

Dimensions

Part No.	Port 1	Port 2	Ø B	C	D	Ø E	F	K	H	I	Ø J	SW
R412010581	Ø 4	M5	4	21.8	4	9	15.9	20.4	12	7.5	8.7	7
R412010582	Ø 6	M5	6	21.8	4	11.1	17.2	21.8	13	7.5	8.7	7
R412010585	Ø 4	G 1/8	4	28.5	5.5	11.5	21.9	28.8	21	9.8	13.6	10
R412010586	Ø 6	G 1/8	6	28.5	5.5	13.5	22.4	29.3	21.7	9.8	13.6	10
R412010587	Ø 8	G 1/8	8	28.5	5.5	15.5	24.2	31.1	22.7	9.8	13.6	10
R412010588	Ø 6	G 1/4	6	33.6	6.5	13	24.3	33.5	25.3	12.8	17.6	13
R412010589	Ø 8	G 1/4	8	33.6	6.5	15.5	26.6	35.5	25.3	11.5	17.6	13
R412010590	Ø 10	G 1/4	10	33.6	6.5	18.1	29.2	38.1	26.7	11.5	17.6	13
R412010591	Ø 8	G 3/8	8	40.8	7	15.6	28.2	40.6	23.6	15.8	22.2	16
R412010592	Ø 10	G 3/8	10	40.8	7	19	32	43.3	33.5	16.4	22.2	16
R412010593	Ø 12	G 3/8	12	40.8	7	22.1	34.2	45.4	35.6	17.8	22.2	16
R412010594	Ø 10	G 1/2	10	47.8	8.3	19.2	34	47.7	41.4	20.3	26.6	18
R412010595	Ø 12	G 1/2	12	47.8	8.3	22	36.1	49.8	43.9	21.5	26.6	18