


WSV

Bulkhead Union Elbow

24° Flareless / 24° Flareless



D = 16mm, max. bulkhead thickness

TUBE FITTING PART #	END SIZE 1 & 2 (mm)	M Metric	d2 (mm)	I 2 (mm)	I 3 (mm)	I 5 (mm)	L 2 (mm)	L 3 (mm)	S 2 (mm)	S 3 (mm)	S 4* (mm)	STANDARD Pressure Rating (bar)			
												EO		EO-2	
												CF	71	MS	CF 71
WSV06L	6	M12 x 1.5	17	12.0	27.0	14	27	42	14	12	17	315	315	200	315
WSV08L	8	M14 x 1.5	19	14.0	27.0	17	29	42	17	12	19	315	315	200	315
WSV10L	10	M16 x 1.5	22	15.0	28.0	18	30	43	19	14	22	315	315	200	315
WSV12L	12	M18 x 1.5	24	17.0	29.0	20	32	44	22	17	24	315	315	200	315
WSV15L	15	M22 x 1.5	27	21.0	31.0	23	36	46	27	19	30	315	315	200	315
WSV18L	18	M26 x 1.5	32	23.5	32.5	24	40	49	32	24	36	315	315	200	315
WSV22L	22	M30 x 2	36	27.5	34.5	30	44	51	36	27	41	160			160
WSV28L	28	M36 x 2	42	30.5	35.5	34	47	52	41	36	46	160			160
WSV35L	35	M45 x 2	50	34.5	36.5	39	56	58	50	41	55	160			160
WSV42L	42	M52 x 2	60	40.0	36.0	43	63	59	60	50	65	160			160
WSV06S	6	M14 x 1.5	19	16.0	29.0	17	31	44	17	12	19	630			630
WSV08S	8	M16 x 1.5	22	17.0	29.0	18	32	44	19	14	22	630			630
WSV10S	10	M18 x 1.5	24	17.5	29.5	20	34	46	22	17	24	630			630
WSV12S	12	M20 x 1.5	27	21.5	30.5	21	38	47	24	17	27	630			630
WSV14S	14	M22 x 1.5	27	22.0	32.0	23	40	50	27	19	30	630			630
WSV16S	16	M24 x 1.5	30	24.5	31.5	24	43	50	30	24	32	400			400
WSV20S	20	M30 x 2	36	26.5	33.5	30	48	55	36	27	41	400			400
WSV25S	25	M36 x 2	42	30.0	35.0	34	54	59	46	36	46	400			400
WSV30S	30	M42 x 2	50	35.5	37.5	39	62	64	50	41	50	400			400
WSV38S	38	M52 x 2	60	41.0	37.0	43	72	68	60	50	65	315			315

* S4 – Hexagon nut according to DIN 80705.

For EO-2 part number, insert "Z" between size and pressure series.

Example: WSV06ZLCF

Dimensions and pressures for reference only, subject to change.