Kraftform Plus - Series 100 VDE

The safety screwdriver for working with live wiring

160 i VDE Insulated screwdriver for slotted screws



Application: Slotted screws

Blade: Insulated, individually tested as per IEC 60900

Design: Conical tip, Lasertip

Handle: Kraftform with non-roll feature, multi-component. "Take it easy"

tool finder: colour coding according to profile (yellow = slotted)

and size stamp.

	J.		[],	₿,	.].	[]',	
	mm	mm	mm	mm			
05 006100 001 ¹⁾	0,4	2,5	80	81	3/32"	3 1/8"	
05 006105 001 1)	0,5	3,0	100	81	1/8"	4"	
05 006110 001	0,6	3,5	100	81	9/64	4"	
05 006115 001	0,8	4,0	100	98	5/ ₃₂ "	4"	
05 006116 001	0,8	4,0	150	98	5/ ₃₂ "	6"	
05 006120 001	1,0	5,5	125	98	7/ ₃₂ "	5"	
05 006121 001	1,0	5,5	200	98	7/ ₃₂ "	8"	
05 006125 001	1,2	6,5	150	105	1/4"	6"	
05 006126 001	1,2	6,5	200	105	1/4"	8"	
05 006130 001	1,2	8,0	175	112	5/_"	7"	
05 006135 001	1,6	8,0	200	112	5/_"	8"	
05 006140 001	1,6	10,0	200	112	3/8"	8"	

¹⁾ without Lasertip

160 i SB VDE Insulated screwdriver for slotted screws

-			4013288
05 100000 001	•	1 x 0.4x2.5x80 ¹⁾	181466
05 100001 001	•	1 x 0.5x3.0x100 1)	181473
05 100002 001	•	1 x 0.6x3.5x100	181480
05 100003 001	•	1 x 0.8x4.0x100	181497
05 100004 001	•	1 x 1.0x5.5x125	181503



160 iS VDE Insulated screwdriver with reduced blade diameter for slotted screws



Application: Slotted screws and actuating tool for spring terminals

Blade: Reduced blade diameter with integrated protective insulation,

allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900

Design: Conical blade, zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. "Take it easy"

tool finder: colour coding according to profile (yellow = slotted)

and size stamp.

	∫ mm	. I. mm	[]; mm	Ωʻ, mm	.].],	
05 006440 001	0,6	3,5	100	81	9/ "	4"	
05 006441 001	0,8	4,0	100	98	5/32"	4"	
05 006442 001	1,0	5,5	125	98	7/32	5"	

160 iSS VDE Insulated screwdriver with reduced blade diameter for slotted screws



Application: Slotted screws and actuating tool for spring terminals

Blade: Reduced blade diameter with integrated protective insulation,

allows sunken screws and spring elements to be accessed and

actuated, individually tested as per IEC 60900

Design: Conical blade, zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. "Take it easy"

tool finder: colour coding according to profile (yellow = slotted)

and size stamp.

] mm	.I. mm	[, mm	Û; mm	.].	[,	
05 020129 001	0,8	4,0	100	81	5/32"	4"	