

Co-1 CORROSION INHIBITOR

Article #	EAN	Product
895118	3660338474897	Corrosion Inhibitor

Description

Protects steel parts and machinery with Spartex Co-1 corrosion inhibitor. Suitable as a pre-treatment for the top coat with alkyd resin-based varnishes that fade in the air. Quick-drying primer for treating untreated ferrometal surfaces. Suitable as a pre-treatment for respraying. The corrosion inhibitor has excellent coverage, filling properties, and adhesion. Co-1 is weldable and easy to sand and provides excellent corrosion prevention. Excellent coverage and filling properties. Suitable for protecting wood. Quick-drying.

Applications

Protection of metal parts against oxidation and corrosion: maintenance, industry, warehouses.

Characteristics

- Gross Volume	650 ml
- Volume net	500 ml
- Propellant	Propane / Butane
- Components	Please refer to the SDS

Instructions

Before use, read the instructions on the package carefully and act accordingly.

The surface should be clean, dry and free of grease. Remove old lacquer and rust and sand the surface.

Best application temperature 5 to 30°C.

Before use, shake the aerosol well for 2 minutes and spray a sample.

Distance to the surface to be treated approx. 20 cm.

Apply the Co-1 corrosion inhibitor in several coats. Before applying the next coat, it is advisable to shake the aerosol.

After use, clean the valve (turn the spray over and press the nozzle for approx. 5 seconds).

The drying time depends on the ambient temperature, the humidity and the thickness of the lacquer applied.

Packaging

- Unit
- Box of 12 aerosols

