

## **TECHNICAL DATASHEET**

# **GLOVES G-GRIP BLUE**

Reference 848156 to 848159




**Size:** 08 - 09 – 10 - 11 **Colour:** Grey / Blue

Description: Cotton and polyester knitted glove with gripped latex coating on palm and

fingers with elastic and ventilated back.

**Materials:** Glove 50% cotton, 50% polyester. Coating: natural latex. Thickness: 1.7 mm.



Gripped latex coating on palm. Rough-textured hand- Snug fit at wrist good abrasion and tear resistance with elastic.

### Instructions for use:

Gloves for mechanical risks, for general use in dry environments, with no chemical, microbiological, electrical or thermal hazards.

#### Limits to use:

Do not use other than for the purpose defined in the instructions for use below. Users are reminded that gloves with very high resistance to traction (level 4) should not be used when there is a risk of grabbing by moving machines. These gloves do not contain any substances known to be carcinogenic or toxic. Contact with the skin may cause allergic reactions in sensitive persons (natural latex, in the cuff wrists of some gloves). In the event of a reaction, cease use and consult a doctor. Before using these gloves, check that they are intact. Replace if necessary.

### Instructions for storage:

Store in a cool, dry place away from frost and light in their original packaging.

#### Performances:

UK CA

These gloves fulfill the requirements of the European Directive 89/686, specially for ergonomics, harmlessness, comfort, airing and flexibility, and fulfill the requirements of the European standards EN420:2003 (dexterity 5) and EN388:2016 (2,1,4,2,X).

**EN388:2016** Protective gloves against mechanical Risks (Levels obtained on the palm)



- 2: Resistance to abrasion (from 0 to 4)
- 1 : Resistance to cut (from 0 to 5)
- 4: Resistance to tear (from 0 to 4)
- 2: Resistance to perforation (from 0 to 4)
- X: Cutting resistance EN ISO (Newton)

EN420:2003+A1:2009 General requirements