

Gr-2 ALUMINIUM GREASE

Article #	EAN	Product
895122	3660338474910	Aluminum Grease

Description

Spartex Gr-2 Aluminium Grease is a high temperature lubricant, penetrating oil, friction & corrosion preventor. Minimize high temperature seizing hazards. Resists high pressure seizing and water steam. Eases assembling & removal of pitched assemblies as well as sealing. Anti corrosion effect, leaving a protective layer on parts such as bolts, nuts, studs exposed to saline atmosphere. Prevents any seizing and pull out hazards for pieces exposed to high temperatures.

Maximum service temperature: 800°C.

Applications

Effective solution for the lubrication, assembly and removal of the following parts: bolts, threads, brake shafts, exhaust collectors, nuts, spring leafs and clamps, gates, cup gaskets, threaded connectors, navel of mining equipment, rolling mills & boilers.

Characteristics

- Gross Volume	650 ml
- Volume net	500 ml
- Propellant	Propane / Butane
- Components	Please refer to the SDS

Instructions

Before use, carefully read the directions on the packaging and act accordingly.

Before use, shake the aerosol.

Spray directly onto parts to be treated from a distance of 20cm and allow to take effect.

Immediate lubricating properties.

Do not spray on hot surfaces.

Packaging

- Unit
- Box of 12 aerosols

