

885 - Drill bits and pullers for stud pulling

885.F: Drill bits.
885.EH: Pullers.



	d ["]	d [mm]	L [mm]	ΔΔ [g]
885.F1	1/8	3,2	65	5
885.F2	3/16	4,8	85	10
885.F3	1/4	6,3	100	20
885.F4	5/16	7,9	115	30
885.F5	11/32	8,7	120	40

	d ["]	d [mm]	L [mm]	ΔΔ [g]
885.EH1	1/4	6,3	-	15
885.EH2	5/16	7,9	-	20
885.EH3	3/8	9,5	-	35
885.EH4	7/16	11,1	-	45
885.EH5	1/2	12,7	-	60


STUD PULLERS

286A - Roller-type stud drivers - Multi-diameter

- Choose the hole suited to the stud diameter.
- Tighten or untighten: thanks to its eccentric shaft, the knob grips the stud, for tightening or untightening.



	C mini - maxi [mm]	Capacity Mini-Maxi [mm]	Square ["]	Dimension [mm]	ΔΔ [g]
286A	5 - 20	5 - 20	1/2	52 x 54	400
286A.PL	15 - 27	15 - 27	3/4	72 x 66	950



287B - Roller-type stud drivers - Single-diameter

- Capacity: Ø 6 to 16 mm.
- Turned by means of the hexagonal drive or a 1/2" - 12.7 mm ratchet. Except model 287B.16, which has a through-hole for a bar.
- Allows to tighten or untighten the studs.



	A maxi [mm]	d [mm]	d1 [mm]	L [mm]	Capacity [mm]	ΔΔ [g]
287B.6	6	25	22	65	6	165
287B.7	7	25	22	65	7	170
287B.8	8	25	22	65	8	170
287B.9	9	29	22	75	9	245
287B.10	10	29	22	75	10	240
287B.12	12	29	22	75	12	240
287B.14	14	34	27	75	14	310
287B.16	16	34	27	75	16	340

