

Bellow gripper DHEB-63-E-U-E-P

Part number: 1320841

FESTO



Data sheet

Feature	Value
Size	63
Stroke of bellows	25 mm
Min. ø to be gripped	66 mm
Max. ø to be gripped	85 mm
Short type code	DHEB
Mounting position	optional
Mode of operation	Single-acting Closed
Design	Contracting diaphragm Force pilot operated motion sequence
Guide	Basic guide
Position detection	Via proximity switch
Operating pressure	4 bar ... 8 bar
Reset pressure	<1 bar
Max. operating frequency of gripper	≤4 Hz
Min. opening time at 6 bar	40 ms
Min. closing time at 6 bar	100 ms
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Corrosion resistance class CRC	2 - Moderate corrosion stress
Ambient temperature	5 °C ... 60 °C
Average replacement interval for the bellows	0.5 MioCyc
Guide value for effective load	5.1 kg
Product weight	785 g
Type of mounting	Either: Via male thread Via lock nut
Pneumatic connection	G1/8
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Material bellows	EPDM
Material housing	Aluminium Anodised