

Unique concept & design for quick and clear lubricant identification eliminating the risk of cross contamination or mixing of incompatible lubricants

Tough, impact and drop resistant polycarbonate tube with aluminium die cast adaptors

High tolerance aluminium die cast head with steel block nut


Super strong pistol grip handle designed to prevent pinching of fingers

### Complete with



4" (100 mm) steel extension & coupler,  
12" (300 mm) × 0.33" (8.5 mm) flexible hose & coupler

Barrel available as spare also

### FEATURES

DEVELOPS	
	<b>UPTO 5,000 PSI (345 BAR)</b>
DELIVERS	
	<b>UPTO 0.50 GM / STROKE (0.70 OZ. / 40 STROKES)</b>

### FILLING OPTIONS

CARTRIDGE LOADING	SUCTION FILL
	



Quick lubricant identification eliminating the risk of mixing incompatible or unspecified lubricants



Clear Tube Barrel only

### ORDERING INFORMATION

CAT NR.	ORD NR.	CARTRIDGE CAPACITY		BULK CAPACITY	THREADS	BOX QTY.
		(OZ.)	(GMS)	(CM³)		
GREASE GUN						
G5RF/B-CL	46920	14	400	500	1/8" BSPT	16
G5RF/M-CL	46921	14	400	500	M10 × 1	16
G5RF/N-CL	46922	14	400	500	1/8" NPT	16
G4RF/PST/B-CL	46923	-	450	650	1/8" BSPT	16
BARREL ONLY						
BRL/G1-CL	46990	Replacement clear tube barrel only 14 oz. (400 gms)			2.2806" × 16 UNF	20
BRL/G4-CL	46991	Replacement clear tube barrel only 450 gms			2.5" × 16 UNF	20

### WARNING

Designed for use with grease only: Do not use with: ESTER based Greases, Synthetic Greases such as Aeroshell 33 Grease, Aeroshell 7 Grease, Skydrol Products etc. These have an adverse effect on the clear polycarbonate tube & can cause fogging, cracking & fracturing of the tube.