

ISO Standards Air Cylinder: Standard

Double Acting, Single Rod

C85 Series

ø8, ø10, ø12, ø16, ø20, ø25

RoHS

How to Order

Double acting, Single rod **C D 85 N 20 - 40 C J L V - B - M9BW S -**

Head cover type

N	Basic (Integrated clevis)
E	Double end boss-cut
F	Boss-cut/Basic
Y	Head cover axial port

Bore size

8	8 mm
10	10 mm
12	12 mm
16	16 mm
20	20 mm
25	25 mm

Applicable head cover

Action	N	E	F	Y
Rubber bumper	●	●	●	●
Air cushion	●*1	—	—	—

Cylinder stroke [mm]

Refer to the next page for standard strokes.

Built-in magnet

Nil	None
D	Built-in magnet

Cushion

Nil	Rubber bumper (Standard)
C	Air cushion

Rod boot (ø20, ø25 only)

Nil	Without rod boot
J	Nylon tarpaulin (One end)
K	Heat resistant tarpaulin (One end)

Accessory*1

Nil	None
V	Rod end
W	Double knuckle joint

*1 Refer to Mounting Brackets/Accessories on page 4 for details of accessories.
* Accessory is shipped together with the product.

Auto switch mounting type*1

A	Rail mounting
B	Band mounting

*1 The symbol is "Nil" for no magnet.

Number of auto switches

Nil	2
S	1
n	n

Auto switch

Nil	Without auto switch
-----	---------------------

* For applicable auto switches, refer to the table below.
* Auto switches are shipped together with the product.

Mounting bracket*1

Nil	None
L	Single foot
M	Double foot
G	Flange
U	Trunnion
N	Clevis

*1 Refer to Mounting Brackets/Accessories on page 4 for details of mounting brackets.
* Mounting bracket is shipped together with the product.

Applicable mounting bracket

Action	Head cover type	L	M	G	U	N
Rubber bumper	N	●	●	●	●	●
	E	●	●	●	●	—
	F	●	—	●	●	—
	Y	●	—	●	●	—
Air cushion	N*1	●	●	●	●	●

*1 Except ø8

Made to order

For details, refer to page 3.

Applicable Auto Switches/Refer to the Web Catalog or Best Pneumatics No. 2-1 for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model				Lead wire length [m]					Pre-wired connector	Applicable load			
Solid state auto switch	—	Grommet	Yes	3-wire (NPN)	5 V, 12 V	—	Band mounting		Rail mounting		0.5 (Nil)	1 (M)	3 (L)	5 (Z)	None (N)	—	IC circuit			
		3-wire (PNP)		Perpendicular			In-line	Perpendicular	In-line											
	Connector	2-wire		12 V	M9BV		M9B	M9BV	M9B	●	●	●	○	○	○	—				
	Diagnostic indication (2-color indicator)	Grommet		3-wire (NPN)	5 V, 12 V		M9NVV	M9NW	M9NVV	M9NW	●	●	●	○	○	○	—			
				3-wire (PNP)			M9PWV	M9PW	M9PWV	M9PW	●	●	●	○	○	○	—			
				2-wire	12 V		M9BWW	M9BW	M9BWW	M9BW	●	●	●	○	○	○	—			
				3-wire (NPN)	5 V, 12 V		M9NAV*1	M9NA*1	M9NAV*1	M9NA*1	○	○	●	○	○	○	—			
				3-wire (PNP)			M9PAV*1	M9PA*1	M9PAV*1	M9PA*1	○	○	●	○	○	○	—			
				2-wire	12 V		M9BAV*1	M9BA*1	M9BAV*1	M9BA*1	○	○	●	○	○	○	—			
	With diagnostic output (2-color indicator)	4-wire (NPN)		5 V, 12 V	—		H7NF	—	F79F	●	—	●	○	—	○	IC circuit				
	Reed auto switch	—		Grommet	Yes		3-wire (NPN equivalent)	—	5 V	—	A96V	A96	A96V	A96	●	—	●	—	—	IC circuit
											—	200 V	—	—	A72	A72H	●	—	●	—
Connector			No	2-wire	24 V	12 V	100 V or less	A93V*2	A93	A93V*2	A93	●	●	●	●	—	—			
							—	—	C73C	A73C	—	●	—	●	●	●	—	—		
Diagnostic indication (2-color indicator)		Grommet	Yes	—	—	—	—	24 V or less	—	C80C	A80C	—	●	—	●	●	—	IC circuit		
								—	—	—	A79W	—	●	—	●	—	—	—	—	
								—	—	—	—	—	—	—	—	—	—	—	—	—

*1 Water resistant type auto switches can be mounted on the above models, but SMC cannot guarantee water resistance.

Please contact SMC regarding water resistant types with the above model numbers.

*2 1 m lead wire is only applicable to the D-A93.

* Lead wire length symbols: 0.5 m..... Nil (Example) M9NW 3 m..... L (Example) M9NWL None..... N (Example) H7CN
1 m..... M (Example) M9NWM 5 m..... Z (Example) M9NWX

* Since there are other applicable auto switches than listed above, refer to page 111 for details.

* Solid state auto switches marked with "○" are produced upon receipt of order.

* D-A9□/M9□/A7□/A80□/F7□/J7□ auto switches are shipped together, but not assembled. (For band mounting, only the auto switch mounting brackets are assembled before shipment.)

* When mounting a band on bore size ø8, ø10, or ø12, the D-A9□(V) cannot be mounted.

* When mounting a rail on bore size ø8, ø10, or ø12, the D-A9□(V) and A79W cannot be mounted.

* When mounting a rail on bore size ø20 or ø25, the D-M9□(V), M9□W(V), and M9□A(V) cannot be mounted.


C85 Series



Symbol

Double acting,
Single rod

Air cushion



Refer to pages 101 to 111 for cylinders with auto switches.

- Auto Switch Proper Mounting Position (Detection at stroke end) and Mounting Height
- Minimum Stroke for Auto Switch Mounting
- Operating Range
- Auto Switch Mounting Brackets/Part No.



Made to Order

(For details, refer to pages 115 to 120.)

Symbol	Specifications
-XA	Change of rod end shape*1
-XB6	Heat resistant cylinder (−10 to 150°C)*2
-XB7	Cold resistant cylinder (−40 to 70°C)
-XB9	Low speed cylinder (10 to 50 mm/s)
-XC4	With heavy duty scraper
-XC6□	Made of stainless steel

*1 Exclude ø8 air cushion.

*2 Rubber bumper ø10 to ø25 only

Specifications

Bore size [mm]		8	10	12	16	20	25
Type		Pneumatic					
Action		Double acting, Single rod					
Fluid		Air					
Proof pressure		1.5 MPa					
Max. operating pressure		1.0 MPa					
Min. operating pressure	Rubber bumper	0.1 MPa	0.08 MPa		0.05 MPa		
	Air cushion	—	0.08 MPa		0.05 MPa		
Ambient and fluid temperature		Without auto switch: −20°C to 80°C (No freezing)					
		With auto switch: −10°C to 60°C (No freezing)					
Lubricant		Not required (Non-lube)					
Stroke length tolerance		$^{+1.0}_0$ mm				$^{+1.4}_0$ mm	
Piston speed		50 to 1500 mm/s					
Cushion		Rubber bumper					
		—	Air cushion				
Allowable kinetic energy	Rubber bumper	0.02 J	0.03 J	0.04 J	0.09 J	0.27 J	0.4 J
	Air cushion	—	0.17 J	0.19 J	0.4 J	0.66 J	0.97 J

Standard Strokes

Bore size [mm]	Standard stroke [mm]*2*4	Max. stroke*3 [mm]
8*1	10, 25, 40, 50, 80, 100	200
10		400
12		
16	10, 25, 40, 50, 80, 100, 125, 160, 200	
20		1000
25	10, 25, 40, 50, 80, 100, 125, 160, 200, 250, 300	

*1 Not available with air cushion.

*2 Other strokes are available on request.

*3 For exceeding the standard stroke range, it will be available as a special order (-X2018).

*4 The minimum stroke with air cushion is 25 mm.

Option: Ordering Example of Cylinder Assembly

Cylinder model: CD85N20-50CNW-B-M9BW

Head cover N: Basic (Integrated clevis)
Mounting bracket N: Clevis
Rod end bracket W: Double knuckle joint
Auto switch D-M9BW: Band mounting, 2 pcs.

* Mounting bracket, double knuckle joint, and auto switch are shipped together with the product.

⚠ Precautions

Be sure to read this before handling the products. Refer to the back cover for safety instructions. For actuator and auto switch precautions, refer to the “Handling Precautions for SMC Products” and the “Operation Manual” on the SMC website: <http://www.smcworld.com>