

Plummer block housing units

RASEY40-TV-VA (Series RASEY..-TV-VA)

plastic housing, radial insert ball bearing with grub screws in inner ring, corrosion-resistant design, R seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

| | |
|----------------|--------------|
| d | 40 mm |
| L | 184 mm |
| H ₂ | 99 mm |
| | |
| A | 54 mm |
| B | 49,2 mm |
| H | 49,2 mm |
| H ₁ | 19,5 mm |
| J | 137 mm |
| N | 14 mm |
| N ₁ | 18 mm |
| Q | 1/4 - 28 UNF |

| | | |
|-------------------|----------------------|--|
| S ₁ | 30,2 mm | |
| m | 1,05 kg | Mass |
| C _r | 31500 N | Basic dynamic load rating, radial |
| C _{0r} | 18900 N | Basic static load rating, radial |
| C _{0r G} | 11100 N | Load carrying capacity of housing, radial |
| | GEH.ASE08-TV | Designation of housing |
| | GYE40-KRR-B-FA107-VA | Designation of bearing |
| | KASK08-S-G | Bearing end cap, closed design. Each housing unit is supplied with an end cap. |
| | KASK08-S-R-NBR | Bearing end caps for housing units, open design, with integral rotary shaft seal. Available by agreement. |



