

7454-1400


Mechanical Torque Wrench with Dial Scale, Fixed Square Drive Head and 2 Sections Handle




PRODUCT DETAILS

- Torque is displayed at every moment during the torque event
- Anti-shock protected dial with dual scales in N·m/ft.lb
- Can be used CW and ACW by turning the dial and slave pointer to the correct position
- Controlled torque application events to ±4%
- Continuous visual signal with slave pointer showing max torque achieved

- 1" fixed square drive
- Delivered in two pieces which need to be assembled for use and calibration
- Delivered in a sturdy metal case with foam
- Supplied with a declaration of conformity
- Made in USA







PRODUCT ATTRIBUTES

| Product: 7454-1400 | | | | | | | |
|--------------------|---------------|--------------|-----|-----|-----|-----|------|
| Product /454-14III | D., | | 4 | = | AFA | 4 4 | 100 |
| | \mathbf{Pr} | \mathbf{O} | шст | - / | 454 | -74 | LCJC |

| Nm Nm | 275-1400 N·m | 1111111 | 200-1000 lbf·ft | | 1 in |
|-------|--------------|---------|-----------------|---|---------|
| Nm Nm | 25 N·m | n-b | 20 lbf·ft | A | 1880 mm |
| В | 1790 mm | C | 1740 mm | D | 64 mm |
| E | 85 mm | F | 50 mm | G | 76 mm |
| kg | 13.620 kg | | | | |