DIELECTRIC PADLOCKS TECHNICAL DATA SHEET

Spartex



A comprehensive range of Dielectric Thermoplastic Safety Padlocks is now available from Spectrum Industrial. Incorporating a non-conductive, non-sparking and non-magnetic Dielectric Nylon shackle, it's a cost effective safety solution for environments where a non-metal construction is needed.

Benefits of Dielectric Padlocks:

- Specifically designed for Lockout Tagout applications
- Conforms to OSHA guideline (1 padlock, 1 key, 1 employee)
- Photoluminescent label
- Thermoplastic body and Nylon shackle
- Colour coded and customisable
- Withstands chemicals, weather and is UV stable
- Key retaining, keyed different 6-pin tumbler cylinder
- Available as master keyed, keyed alike and keyed alike-master keyed

Product Specification

Description: Dielectric Safety Padlock

Colours: Red, Yellow, Green, Blue, Black, Orange

Size: Width:

Body Height: 45 mm
Shackle Height: 40 mm
Shackle Diameter: 6 mm

42 mm

Key: KD as standard

Custom Engraving and Identification

We offer customisation on our Lockout Tagout safety equipment. Padlocks can be laser etched with names, registration numbers, company details or other identifying information. We also offer custom printed labels which can include a user photo as means of identification.







Colour	Code
Red	LOK068
Yellow	LOK263
Green	LOK264
Blue	LOK265
Black	LOK266
Orange	LOK267

