

NON CORROSIVE

Non corrosive



Features:

Ideal for retrofit of existing T5 or T8 fixtures

3 lengths available

Integral emergency option available

Polycarbonate body finished in Grey

Stainless steel fixing clips

Supplied with opal diffuser

CRI: Ra>80

30,000 hours lifetime [L70/B50]

Construction:

Up to 131 lumens per watt efficacy

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, a



NON CORROSIVE

Non corrosive

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCNC14NW	1200 mm Non Corrosive - 4000K	2600	24	108	1.8
XCNC24NW	1200 mm Non Corrosive - 4000K	5100	48	106	2.5
XCNC15NW	1500 mm Non Corrosive - 4000K	4000	36	111	2.1
XCNC25NW	1500 mm Non Corrosive - 4000K	8000	71	113	3.4
XCNC16NW	1800 mm Non Corrosive - 4000K	4400	39	113	3.0
XCNC26NW	1800 mm Non Corrosive - 4000K	8400	79	106	4.3
XCNC14HENW	1200 mm Non Corrosive - 4000K	4500	36	125	1.8
XCNC15HENW	1500 mm Non Corrosive - 4000K	6300	48	131	2.5
XCNC16HENW	1800 mm Non Corrosive - 4000K	7900	63	125	3.0

Dimensions

All dimensions are in millimetres

Order Code	A	B	Height	Fixing Centre
XCNC14NW	1260	98	93	1000
XCNC24NW	1260	154	95	1000
XCNC15NW	1560	98	93	1200
XCNC25NW	1560	154	95	1200
XCNC16NW	1830	100	101	1000
XCNC26NW	1830	158	102	1000
XCNC14HENW	1260	98	93	1000
XCNC15HENW	1560	98	93	1200
XCNC16HENW	1830	100	101	1000

