

GLOVE G-DRIVER CRUST

| Item # | EAN | Product |
|---------------|---------------|---------|
| 840008 | 3660338055737 | SIZE 8 |
| 840009 | 3660338055744 | SIZE 9 |
| 840010 | 3660338055751 | SIZE 10 |
| 840011 | 3660338055768 | SIZE 11 |

Description

COWHIDE LEATHER GRAIN PALM GLOVE / GREY COWHIDE BACK

Colour: Grey

American cut glove, cowhide leather grain palm, cowhide back, elasticated cuff.

Materials:

Palm: grey cowhide leather grain (thickness: 0.9mm to 1.1mm).

Back : grey split leather.(thickness: 0.9mm to 1.1mm)

Characteristics

- General use reinforced mechanical protection gloves Slip leather back. Welt- reinforced seams.



Instructions & storage

Instructions for use:

Gloves for mechanical risks, for general use in dry environments, with no chemical, microbiological, electrical or thermal hazards

Limits to use:

Do not use other than for the purpose defined in the instructions for use below. *Users are reminded that gloves with very high resistance to traction (level 4) should not be used when there is a risk of grabbing by moving machines. These gloves do not contain any substances known to be carcinogenic or toxic. Contact with the skin may cause allergic reactions in sensitive persons (natural latex, in the cuff wrists of some gloves). In the event of a reaction, cease use and consult a doctor. Before using these gloves, check that they are intact. Replace if necessary.

Instructions for storage:

Store in a cool, dry place away from frost and light in their original packaging.

Standards and certifications

UK
CA

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 3 : Resistance to abrasion (from 0 to 4)
- 1 : Resistance to cut (from 0 to 5)
- 4 : Resistance to tear (from 0 to 4)
- 3 : Resistance to perforation (from 0 to 4)
- x : Cutting resistance EN ISO (Newton)

Packaging

- Packed in 12 pairs/ 120 pairs in a carton