

One-touch Fittings

Series KQ2

Applicable Tubing: Metric Size
Connection Thread: M, R, Rc

How to Order

KQ 2 H 06 - 01 S -

One-touch fittings

Product's color

Symbol	Body	Release button
2	White	Light gray
Nil	Black	Blue

• Made to Order
Refer to page 58 for details.

• With thread sealant (Male thread only)

Nil	None
S	With thread sealant

Note) Port size with sealant: Only
R 1/8
R 1/4
R 3/8
R 1/2

• Applicable tubing O.D.

	O.D.
23	ø3.2
04	ø4
06	ø6
08	ø8
10	ø10
12	ø12
16	ø16

• Port size/Applicable tubing O.D.

Thread connection	Port size	Applicable tubing O.D.
M5	M5 x 0.8	
M6	M6 x 1.0	
01	R 1/8, Rc 1/8	
02	R 1/4, Rc 1/4	
03	R 3/8, Rc 3/8	
04	R 1/2, Rc 1/2	
00	Same dia. tubing	
04	ø4	(Reducer) Different dia. tubing
06	ø6	
08	ø8	
10	ø10	
12	ø12	
16	ø16	
99	Same dia. rod	

• Model

Accessory

Symbol	Name
	Nipple
KQ2N	Reducer nipple
	Adaptor
KQ2C	Tube cap
KQ2C	Color cap
KQ2P	Plug (White)
KQP	Plug (Blue)

Use the below part number to order the gasket for M5 and M6 threads.

Gasket for M5 thread: M-5G2

Gasket for M6 thread: M-6G

H	Male connector	T	Male branch tee
	Straight union		Union tee
	Different diameter straight		Different diameter tee*
S	Hex. socket head male connector	TW	Cross*
F	Female connector	TX	Different diameter cross*
L	Male elbow	TY	Different diameter cross*
	Union elbow	Y	Male run tee
	Plug-in elbow	D	Male delta union
	Reducer elbow		Delta union
LU	Male branch connector	U	Branch "Y"
	Branch union elbow		Union "Y"
K	45° male elbow		Different dia. union "Y"
V	Universal male elbow		Plug-in "Y"
VS	Hexagon socket head universal male elbow		Delta branch
VF	Universal female elbow	UD	Different dia. double union "Y"
LF	Female elbow	XD	Double plug-in "Y"
VD	Double universal male elbow	X	Different diameter plug-in "Y"
VT	Triple universal male elbow	R	Plug-in reducer
Z	Branch universal male elbow	E	Bulkhead union
ZF	Branch universal female elbow		Bulkhead connector
ZD	Double branch universal male elbow		Bulkhead male elbow
ZT	Triple branch universal male elbow		
W	Extended plug-in elbow		
	Extended male elbow		

* Available only for white color body.


Series KQ2

Male Connector: KQ2H



Applicable tubing O.D. (inch)	Connection thread UNF NPT	Model	H (Width across flats)	Note) øD	L	A*	M	Min. port size	Mass (g)
1/8	10-32 UNF	KQ2H01-32	7	—	16.7	13.7	12.7	2.3	2
	1/16	KQ2H01-33S	11.11	—	22	18	15.5	2.5	7
	1/8	KQ2H01-34S	—	—	21.1	—	—	—	9
	1/4	KQ2H01-35S	14.29	—	19	13.5	—	—	16
5/32	10-32 UNF	KQ2H03-32	8	—	17	14	12.7	2.3	2.4
	1/16	KQ2H03-33S	11.11	—	22	18	16	3	7
	1/8	KQ2H03-34S	—	—	21.1	—	—	—	9
	1/4	KQ2H03-35S	14.29	—	19	13.5	—	—	16
3/16	10-32 UNF	KQ2H05-32	8	11	24	20.4	16.5	2.3	6
	1/8	KQ2H05-34S	12.7	—	21.1	18	—	3.5	11
	1/4	KQ2H05-35S	14.29	—	20.5	15	—	—	12
	10-32 UNF	KQ2H07-32	11.11	—	18.4	15.4	13.6	2.3	3.3
1/4	1/8	KQ2H07-34S	12.7	—	21.6	18.5	17	4.6	10
	1/4	KQ2H07-35S	14.29	—	22.5	17	—	—	15
	3/8	KQ2H07-36S	17.46	—	20.9	16.5	—	—	27
	1/8	KQ2H09-34S	14.29	—	27.6	24.5	18.5	6	15
5/16	1/4	KQ2H09-35S	—	—	26	20.5	—	—	16
	3/8	KQ2H09-36S	17.46	—	20.9	15.5	—	—	24
	1/8	KQ2H11-34S	—	—	29.6	26.5	21	6	29
	1/4	KQ2H11-35S	17.46	—	33	27.5	—	—	31
3/8	3/8	KQ2H11-36S	—	—	27.9	22.5	—	7	29
	1/2	KQ2H11-37S	22.23	—	25.6	18.5	—	—	46
	1/4	KQ2H13-35S	—	—	34	28.5	22	9	44
	3/8	KQ2H13-36S	22.23	—	31.9	26.5	—	9.6	44
1/2	1/2	KQ2H13-37S	—	—	29.1	22	—	—	44

* Reference dimensions after NPT thread installation.
Note) øD: Max. diameter




Hexagon Socket Head Male Connector: KQ2S



Applicable tubing O.D. (inch)	Connection thread UNF NPT	Model	H (Width across flats)	Note) øD	L	A*	M	Min. port size	Mass (g)
1/8	10-32 UNF	KQ2S01-32	2	7	19.7	16.6	12.7	2	2.8
	10-32 UNF	KQ2S03-32	2.5	8	18.7	15.6	12.7	2.3	2.7
5/32	1/8	KQ2S03-34S	2.78	10.5	23.5	19.5	16	2.8	8
	1/8	KQ2S05-34S	3.57	10.7	23.5	19.5	16.5	3.6	8
3/16	10-32 UNF	KQ2S07-32	2.5	10.3	19.6	16.5	13.6	2.3	3.3
	1/8	KQ2S07-34S	—	12.5	22	18	—	—	7
	1/4	KQ2S07-35S	4.76	13.8	23	17	17	4.9	12
	3/8	KQ2S07-36S	—	17	27	21	—	—	27
5/16	1/8	KQ2S09-34S	5.56	—	28	24	—	5.7	12
	1/4	KQ2S09-35S	6.35	14	25.5	19.5	18.5	6.5	11
	3/8	KQ2S09-36S	—	17.5	27.5	21	—	—	25
	1/8	KQ2S11-34S	5.56	16.5	30	26	21	5.7	17
3/8	1/4	KQ2S11-35S	6.35	16.5	32	26	—	—	21
	3/8	KQ2S11-36S	6.35	17.2	29	23	21	6.5	25
	1/2	KQ2S11-37S	—	21.3	30	22	—	—	45
	1/4	KQ2S13-35S	7.94	20	34.5	28.5	22	8	26
1/2	3/8	KQ2S13-36S	9.53	—	33	26.5	—	—	27
	1/2	KQ2S13-37S	—	21.3	31	22.5	22	9.6	36

* Reference dimensions after NPT thread installation.
Note) øD: Max. diameter



Female Connector: KQ2F



Applicable tubing O.D. (inch)	Connection thread UNF NPT	Model	H (Width across flats)	Note) øD	L1	L2	M	Min. port size	Mass (g)
1/8	1/8	KQ2F01-34	14.29	9.2	26.5	11.5	15.5	2.5	16
	1/4	KQ2F01-35	17.46	—	30.5	14.5	—	—	26
5/32	1/8	KQ2F03-34	14.29	10	27	11	16	3	15
	1/4	KQ2F03-35	17.46	—	31	13.5	—	—	24
1/4	1/8	KQ2F07-34	14.29	—	27.5	10.5	—	—	17
	1/4	KQ2F07-35	17.46	12.5	31	13.5	17	4.6	25
	3/8	KQ2F07-36	22.23	—	33.5	15.5	—	—	44
	1/8	KQ2F09-34	14.29	—	29	10.5	—	—	18
5/16	1/4	KQ2F09-35	17.46	14	32.5	13.5	18.5	6	26
	3/8	KQ2F09-36	22.23	—	34.5	13	—	—	38
	1/4	KQ2F11-35	17.46	—	34.5	15	—	—	30
	3/8	KQ2F11-36	22.23	16.5	36.5	19	21	7	48
1/2	1/2	KQ2F11-37	23.81	—	40.5	19	—	—	52
	3/8	KQ2F13-36	22.23	20	36.5	14.5	22	9.6	48
	1/2	KQ2F13-37	23.81	—	41	18.5	—	—	53

Note) øD: Max. diameter

