



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 850, Tapered Roller Bearings - Single Cones - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	835
Cone Part Number	850
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions)¹	190000 lbf 844000 N
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions)²	49200 lbf 219000 N



Dimensions

d - Cone Bore	3 1/2 in 88.9 mm
B - Cone Width	2.2190 in 56.363 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius³	0.140 in 3.6 mm
da - Cone Frontface Backing Diameter	3.94 in 100 mm
db - Cone Backface Backing Diameter	4.17 in 106 mm
Ab - Cage-Cone Frontface Clearance	0.1 in 2.5 mm
Aa - Cage-Cone Backface Clearance	0.13 in 3.3 mm
a - Effective Center Location⁴	-0.73 in -18.5 mm

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁵	28300 lbf 126000 N
C1 - Dynamic Radial Rating (1 million revolutions)⁶	109000 lbf 485000 N
C0 - Static Radial Rating	117000 lbf 522000 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁷	14500 lbf 64400 N

Factors

K - Factor⁸	1.95
G1 - Heat Generation Factor (Roller-Raceway)	197.9
G2 - Heat Generation Factor (Rib-Roller End)	34.8
Cg - Geometry Factor⁹	0.0937

¹ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

² Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

³ These maximum fillet radii will be cleared by the bearing corners.

⁴ Negative value indicates effective center inside cone backface.


⁵ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.

⁶ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁷ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ Geometry constant for Lubrication Life Adjustment Factor a_3 .



IMPERIAL UNITS

Number of Rollers Per Row16	TIMIKEN® THE TIMKEN COMPANY NORTH CANTON, OHIO USA	850 Tapered Roller Bearings - Single Cones - Imperial K Factor Dynamic Radial Rating - C90 Dynamic Thrust Rating - Ca90 Dynamic Radial Rating - C1 1.95 28300 lbf 14500 lbf 109000 lbf
Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.		FOR DISCUSSION ONLY