

Torpedo® In-line Crimp Type Connector Cable Joint

BS EN 50393
TESTED

TOR70 Straight Torpedo® joint with B.S. tested 70mm² crimp connectors.

Low Cost Range

- New 5 core Torpedo® tongue and groove cable joints.
- Low cost, high quality straight through Torpedo® cable joints.
- Offered for colour to colour in-line cable jointing only.
- Each kit supplied as standard with 4 British Standard tested flared end non-indent crimp connectors.
- All Torpedo® cable joints are supplied complete with the Birkett premium earth continuity kit tested to screen short circuit requirements of BS EN 50393.
- Supplied with Birkett Swishpak® 2 part polyurethane resin.

Straight Torpedo® Joint Selection Chart					
Nominal area of conductor (mm²)					
	1 Core Armoured	2 Core Armoured	3 Core Armoured	4 Core Armoured	5 Core Armoured
■ 1.5	TOR6	TOR6	TOR6	TOR6	TOR6*
■ 2.5	TOR6	TOR6	TOR6	TOR6	TOR6*
■ 4	TOR6	TOR6	TOR6	TOR6	TOR6*
■ 6	TOR6	TOR6	TOR6	TOR6	TOR6*
■ 10	TOR6*	TOR6*	TOR10	TOR10	TOR10*
■ 16	TOR6*	TOR10*	TOR16	TOR16	TOR16*
■ 25	TOR6*	TOR16*	TOR25	TOR25	TOR25*
■ 35	TOR6*	TOR25*	TOR35	TOR35	TOR35*
■ 50	TOR6*	TOR35*	TOR35*	TOR70*	TOR70*
■ 70	TOR10*	TOR70	TOR70	TOR70	TOR95*
■ 95	TOR16*	TOR95	TOR95	TOR95	TOR150*
■ 120	TOR16*	TOR95*	TOR150*	TOR150*	TOR240*
■ 150	TOR25*	TOR150	TOR150	TOR150	TOR300*
■ 185	TOR35*	TOR150*	TOR240*	TOR240*	TOR300*
■ 240	TOR35*	TOR240	TOR240	TOR240	TOR400*
■ 300	TOR70*	TOR240*	TOR300	TOR300	TOR400*
■ 400	TOR70*	TOR300*	TOR300*	TOR400	TOR400*
■ 500	TOR95*	—	—	—	—
■ 630	TOR150*	—	—	—	—

Straight Torpedo® Joint Dimensions				
Straight Kit Reference				
	Maximum Core Size (mm²)	Maximum Cable Diameter (mm)	External Length (mm)	External Width (mm)
■ TOR6	6 x 5 Core	27	195	45
■ TOR10	10 x 5 Core	33	210	61
■ TOR16	16 x 5 Core	39	226	71
■ TOR25	25 x 5 Core	39	256	71
■ TOR35	35 x 5 Core	39	325	80
■ TOR70	70 x 4 Core	48	400	90
■ TOR95	95 x 4 Core	45	575	165
■ TOR150	150 x 4 Core	53	630	190
■ TOR240	240 x 4 Core	62	735	210
■ TOR300	300 x 4 Core	73	885	235
■ TOR400	400 x 4 Core	80	960	295

As standard, all Torpedo® kits are supplied with cable connectors to suit the maximum 4 core cable configuration.

* Denotes that the kit will accommodate the cable size shown but the cable size must be advised when ordering to ensure correct connectors are supplied.