

TECHNICAL DATASHEET

Update : 26/02/2019

4 VARI FLUTE CARBIDE END MILL - STANDARD SERIES - STRAIGHT SHANK - OZMAX



Characteristics

Ref.	EAN	Diameter mm	Type of tail	Tail diameter mm	Number of teeth	Length of cut mm	Total length mm	Angle of helix °	Centre cut	Coating	Chamfer mm
862827	3660338174759	3	Cylindrical HA	6	4	8	57	35/38	Yes	OZMAX	0,1
862828	3660338174766	4	Cylindrical HA	6	4	11	57	35/38	Yes	OZMAX	0,13
862829	3660338174773	5	Cylindrical HA	6	4	13	57	35/38	Yes	OZMAX	0,18
862830	3660338174780	6	Cylindrical HA	6	4	13	57	35/38	Yes	OZMAX	0,2
862831	3660338174797	8	Cylindrical HA	8	4	19	63	35/38	Yes	OZMAX	0,2
862832	3660338174803	10	Cylindrical HA	10	4	22	72	35/38	Yes	OZMAX	0,3
862833	3660338174810	12	Cylindrical HA	12	4	26	83	35/38	Yes	OZMAX	0,3
862834	3660338174827	14	Cylindrical HA	14	4	26	83	35/38	Yes	OZMAX	0,3
862835	3660338174834	16	Cylindrical HA	16	4	32	92	35/38	Yes	OZMAX	0,4
862836	3660338174841	18	Cylindrical HA	18	4	32	92	35/38	Yes	OZMAX	0,4
862837	3660338174858	20	Cylindrical HA	20	4	38	104	35/38	Yes	OZMAX	0,5