Auto Switch Mounting Brackets/Part No.

A. da a suitala assaula l	Bore size (mm)					
Auto switch model	ø 20	ø 25	ø 32	ø 40		
D-M9□(V) D-M9□W(V) D-A9□(V)	BM5-020 (A set of a, b, c, d)	BM5-025 (A set of a, b, c, d)	BM5-032 (A set of a, b, c, d)	BM5-040 (A set of a, b, c, d)		
D-M9 □ A(V) Note 2)	BM5-020S (A set of b, c, d, e)	BM5-025S (A set of b, c, d, e)	BM5-032S (A set of b, c, d, e)	BM5-040S (A set of b, c, d, e)		
Switch bracket (Resin) Transparent (Nylon) Note 1) White (PBT) B Switch holder (Zinc) Auto switch Auto switch mounting screw						
D-H7□ D-H7□W D-H7NF D-C7□/C80 D-C73C/C80C	BM2-020A (A set of band and screw)	BM2-025A (A set of band and screw)	BM2-032A (A set of band and screw)	BM2-040A (A set of band and screw)		
D-H7BA	BM2-020AS (A set of band and screw)	BM2-025AS (A set of band and screw)	BM2-032AS (A set of band and screw)	BM2-040AS (A set of band and screw)		
D-B5□/B64 D-B59W D-G5NT	BA2-020 (A set of band and screw)	BA2-025 (A set of band and screw)	BA2-032 (A set of band and screw)	BA2-040 (A set of band and screw)		
D-A3 A/A44A Note 3) D-G39A/K39A	BM3-020 (A set of band and screw)	BM3-025 (A set of band and screw)	BM3-032 (A set of band and screw)	BM3-040 (A set of band and screw)		

Note 1) Since the switch bracket (made from nylon) are affected in an environment where alcohol, chloroform, methylamines, hydrochloric acid or sulfuric acid is splashed over, so it cannot be used. Please contact SMC regarding other chemicals.

Band Mounting Brackets Set Part No.

Set part no.	Contents			
BM2-□□□A(S) * S: Stainless steel screw	Auto switch mounting band (c)Auto switch mounting screw (d)			
BJ4-1	Switch bracket (White/PBT) (e) Switch holder (b)			
BJ5-1	• Switch bracket (Transparent/Nylon) (a) • Switch holder (b)			

Other than the applicable auto switches listed in "How to Order", the following auto switches are mountable.

Refer to the WEB catalog or the Best Pneumatics No. 2 for the detailed specifications.

Туре	Model	Electrical entry	Features
Solid state	D-H7A1, H7A2, H7B		_
	D-H7NW, H7PW, H7BW	Crommet (In line)	Diagnostic indication (2-color indication)
	D-H7BA	Grommet (In-line)	Water resistant (2-color indication)
	D-G5NT		With timer
Reed	D-B53, C73, C76	Grommet (In-line)	_
	D-C80	Grommer (m-ine)	Without indicator light

^{*} With pre-wired connector is also available for solid state auto switches. For details, refer to the **WEB catalog** or the Best Pneumatics No. 2.

ı

Note 2) As the indicator LED is projected from the switch unit, indicator LED may be damaged if the switch bracket is fixed on the indicator LED.

Note 3) The D-A3□A/A44A/G39A/K39A cannot be mounted on the centralized piping type CDM2□P series.

^{*} Normally closed (NC = b contact) solid state auto switches (D-F9G/F9H) are also available. For details, refer to the WEB catalog or the Best Pneumatics No. 2.