


Self-Lube cast iron flange bearing units with adapter sleeves

MSFT 1000-K Series



Shaft diameter mm inches	RHP designation complete unit	Sleeve nut & lockwasher only	Unit without sleeve, nut & lockwasher	Basic bearing insert	Casting group	Dimensions (mm)		
						L	H	J
20	MSFT1025-20K	H305	MSFT1025K	1025	SFT3	68.3	123.8	99.0
3/4	MSFT1025-3/4K	HE305-3/4						
25	MSFT1030-25K	H306	MSFT1030K	1030	1	82.6	141.3	116.5
15/16	MSFT1030-15/16K	HE306-15/16						
1	MSFT1030-1K	HE306-1						
30	MSFT1035-30K	H307	MSFT1035K	1035	2	95.5	155.5	130.0
1 1/8	MSFT1035-1 1/8K	HE307-1 1/8						
1 3/16	MSFT1035-1 3/16K	HE307-1 3/16						
35	MSFT1040-35K	H308	MSFT1040K	1040	3	101.6	171.4	143.5
1 1/4	MSFT1040-1 1/4K	HE308-1 1/4						
1 3/8	MSFT1040-1 3/8K	HE308-1 3/8						
40	MSFT1045-40K	H309	MSFT1045K	1045	4	111.1	179.4	148.5
1 7/16	MSFT1045-1 7/16K	HE309-1 7/16						
1 1/2	MSFT1045-1 1/2K	HE309-1 1/2						
45	MSFT1050-45K	H310	MSFT1050K	1050	5	115.9	188.9	157.0
1 11/16	MSFT1050-1 11/16K	HE310-1 11/16						
1 3/4	MSFT1050-1 3/4K	HE310-1 3/4						
50	MSFT1055-50K	H311	MSFT1055K	1055	6	127.0	215.9	184.0
1 15/16	MSFT1055-1 15/16K	HE311-1 15/16						
2	MSFT1055-2K	HE311-2						

Please check availability

Dimensions (mm)						ISO Load ratings		Rec. max. speed	Mass (approx.)
G	A	A4	A5	B5	d4	dynamic Cr newtons	static Cor newtons	rev/min	kg
10	28.6	11.1	36.5	29.0	38.0	14000	7880	6250	0.9
10	29.8	12.7	38.0	31.0	45.0	19500	11300	5300	1.1
12	32.0	12.7	40.5	35.0	52.0	25700	15300	4500	1.4
12	34.9	12.7	45.0	36.0	58.0	32500	19900	4000	1.9
16	35.3	14.3	46.5	39.0	65.0	32500	20500	3700	2.2
16	39.7	14.3	52.0	42.0	70.0	35000	23200	3400	2.5
16	43.7	17.5	55.5	45.0	75.0	43500	29200	3100	3.5