

### Lu-5 DRY PTFE LUBRICANT

Article #	EAN	Product
895134	3660338474972	Dry PTFE Lubricant

#### Description

Loosen stuck parts with Lu-5 Spartex DRY PTFE LUBRICANT and make sure that chains, hinges, gears, etc. run smoothly. DRY PTFE LUBRICANT offers outstanding mechanical & thermal stability to both metal & plastics moving parts. Lu-5 has a low friction factor, a fine particle size (5µm) and excellent adhesion. Lu-5 is resistant to the weather & weak acids & bases. It is also resistant to temperatures of -50°C up to +250°C.

#### Applications

Lubricates chains, gear wheels, door hinges, industrial vacuum pumps, rails, conveyors, sliding door guides, fastenings, (Agricultural) machinery, rubber seals. Chains, Gear wheels, Door hinges, pedals.

#### Characteristics

- Gross Volume	650 ml
- Volume net	500 ml
- Propellant	Propane / Butane
- Components	Please refer to the SDS

#### Instructions

Before use, carefully read the directions on the packaging and act accordingly.

Best application temperature 10 to 25°C.

Before use, shake the aerosol well for 2 minutes and spray a sample.

Apply Lu-5 DRY PTFE LUBRICANT in a thin layer.

The optimum lubrication is obtained after evaporation of the solvent.

#### Packaging

- Unit
- Box of 12 aerosols

