



SuperTLink® Belting



Wedge

Wedge Cross Section

SUPERTLINK BELTING	Wedge Cross Section	Nominal Width		Part Numbers				Minimum Pulley Ø		Ride Height Above Rim			
		inches	mm	5m	25'	100'	20m	inches	mm	Min(in.)	Max(in.)	Min(mm)	Max(mm)
SuperTLink	3V	0.45	11		0407025	0407100		2.8		0.18	0.40	4.6	10.0
SuperTLink	5V	0.66	17		0417025	0417100		5.5		0.06	0.20	1.4	5.1
SuperTLink	SPZ		10	L02Z5N			L02Z20N		71	0.18	0.40	4.6	10.0
SuperTLink	SPA		13	L02A5N			L02A20N		90	0.14	0.36	3.6	9.1
SuperTLink	SPB	0.66	17	L02B5			L02B20		140	0.06	0.20	1.4	5.1
SuperTLink	SPC		22	L02C5			L02C20		224	0.05	0.33	1.3	8.4
TLink Installation Tool	L02NT10 (10pk)												

Power Transmission - NuTLink®

LINK BELTING



NuTLink® Belting



Classical Cross Section

NUTLINK BELTING	Classical Cross Section	Nominal Width		Part Numbers		Minimum Pulley Ø		Ride Height Above Rim			
		inches	mm	5m	20m	inches	mm	Min(in.)	Max(in.)	Min(mm)	Max(mm)
NuTLink	Z/10		10	L01Z5	L01Z20		45	0.06	0.18	1.6	4.6
NuTLink	A/13	1/2	13	L01A5	L01A20	3.00	80	0.08	0.31	2.0	7.8
NuTLink	B/17	5/8	17	L01B5	L01B20	5.00	125	0.09	0.37	2.2	9.3
NuTLink	C/22	7/8	22	L01C5	L01C20	9.00	229	0.00	0.23	0.1	5.8
TLink Installation Tool	L02NT10 (10pk)										