

Multipole plug, series CON-MP

- open cable ends 25-pin
- with cable
- unshielded



Ambient temperature min./max.	-20 ... 80 °C
Operational voltage	24 V DC
Protection class	IP67
Wire cross-section	0,22 mm ²
Weight	See table below

Technical data

Part No.	Electrical connection	Max. current	Number of wires	Cable sheath
	1			
R419500454	Socket D-Sub 25-pin straight 180°	3 A	25	Polyvinyl chloride
R419500455	Socket D-Sub 25-pin straight 180°	3 A	25	Polyvinyl chloride
R419500456	Socket D-Sub 25-pin straight 180°	3 A	25	Polyvinyl chloride
R412022156	Socket D-Sub 25-pin straight 180°	3 A	25	Polyvinyl chloride
R419500457	Socket D-Sub 25-pin straight 180°	3 A	25	Polyurethane
R419500458	Socket D-Sub 25-pin straight 180°	3 A	25	Polyurethane
R419500459	Socket D-Sub 25-pin straight 180°	3 A	25	Polyurethane
R419500460	Socket D-Sub 25-pin angled 90°	3 A	25	Polyvinyl chloride
R419500461	Socket D-Sub 25-pin angled 90°	3 A	25	Polyvinyl chloride
R419500462	Socket D-Sub 25-pin angled 90°	3 A	25	Polyvinyl chloride
R412022352	Socket D-Sub 25-pin angled 90°	3 A	25	Polyvinyl chloride
R419500463	Socket D-Sub 25-pin angled 90°	3 A	25	Polyurethane
R419500464	Socket D-Sub 25-pin angled 90°	3 A	25	Polyurethane
R419500465	Socket D-Sub 25-pin angled 90°	3 A	25	Polyurethane

Part No.	Bending radius min.	Cable-Ø	Cable length	Weight		Fig.
R419500454	-	8,5 mm	3 m	0,465 kg	-	Fig. 1
R419500455	-	8,5 mm	5 m	0,731 kg	-	Fig. 1
R419500456	-	8,5 mm	10 m	1,373 kg	-	Fig. 1
R412022156	-	8,5 mm	15 m	2,002 kg	-	Fig. 1
R419500457	78,75 mm	10,5 mm	3 m	0,51 kg	1)	Fig. 1
R419500458	78,75 mm	10,5 mm	5 m	0,789 kg	1)	Fig. 1
R419500459	78,75 mm	10,5 mm	10 m	1,491 kg	1)	Fig. 1
R419500460	-	8,5 mm	3 m	0,46 kg	-	Fig. 2
R419500461	-	8,5 mm	5 m	0,707 kg	-	Fig. 2
R419500462	-	8,5 mm	10 m	1,334 kg	-	Fig. 2