



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 3876, Tapered Roller Bearings - Single Cones - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	3800
Cone Part Number	3876
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) ¹	48600 lbf 216000 N
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) ²	12600 lbf 56100 N

Dimensions

d - Bore	1.5 in 38.1 mm
B - Cone Width	1.1875 in 30.163 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius³	0.14 in 3.600 mm
da - Cone Frontface Backing Diameter	1.91 in 48.5 mm
db - Cone Backface Backing Diameter	2.17 in 55 mm
Ab - Cage-Cone Frontface Clearance	0.11 in 2.8 mm
Aa - Cage-Cone Backface Clearance	0.04 in 1 mm
a - Effective Center Location⁴	-0.32 in -8.1 mm

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁵	7240 lbf 32200 N
C1 - Dynamic Radial Rating (1 million revolutions)⁶	27900 lbf 124000 N
C0 - Static Radial Rating	33200 lbf 148000 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁷	4980 lbf 22200 N

Factors

K - Factor⁸	1.45
Cg - Geometry Factor⁹	0.0873

¹ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

² Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

³ These maximum fillet radii will be cleared by the bearing corners.

⁴ Negative value indicates effective center inside cone backface.

⁵ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.

⁶ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁷ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ Geometry constant for Lubrication Life Adjustment Factor a_3 .

