


Multi-subbases for solenoid actuators 3/2 PS1-E24...

Operating pressure 0 to 10 bar

	Connections	Number of positions	Weight Kg	Order code	D
	common air supply	2	0,095	PVU-H13152	3
		4	0,150	PVU-H13154	3
		6	0,200	PVU-H13156	3
	1 G1/8	8	0,255	PVU-H13158	3
	2 M5	10	0,310	PVU-H131510	3

Air Pilot Connectors

	Mounting	Type of connection	Weight Kg	Order code	D
	Mounts on the same interface as the 1 W / 1,2 VA solenoid actuator	Push-in Ø4 mm	0,007	PVA-P111	1
		Threaded M5	0,002	PVA-P115	3

Intermediate Air Pilot Connectors

For mounting between the PVA-H24I solenoid actuator and the PVL-BI or PVL-CI power valve 5/2 mounted on DIN rail

	Description	Type of connection	Weight Kg	Order code	D
	For pneumatic piloting of the power valve	Straight, Push-in Ø4 mm	0,040	PVA-P171	3
	For external air supply to the 1 W / 1,2 VA miniature solenoid actuators	Swivel, Push-in Ø 4 mm	0,040	PVA-P161	1
		Straight, Push-in Ø 4 mm	0,040	PVA-P163	3