

Technical data

ESPG206


Bearing units

Grey cast housing, radial insert ball bearing with eccentric locking collar, single lip seal

KIT CONTENT

ES206G2, PG206

VISUAL (S)



PRODUCT DEFINITION

A - Housing width	48 mm
A1 - Housing top width	25 mm
B - Width of Inner Ring	23,8 mm
d - Shaft diameter	30 mm
d1 - Outer dia of eccent. Lock. collar / nut of adapter sleeve	44,1 mm
E - Mounting hole thread depth	18 mm

PRODUCT DEFINITION

G - Grease fitting	M6x1
H - Distance mounting base to centerline spheric. seating diam.	42,9 mm
H1 - Housing foot height	17 mm
H2 - Housing height	83 mm
J - Mounting holes distance	60 mm
L - Housing length	85 mm
L1 - Housing foot length	25 mm
N - Mounting hole dimension	M10
S - Dist. cent. of raceway to face IR on side opp. lock. device	9 mm
Brand	SNR

PRODUCT PERFORMANCE

C - Dynamic load rating	19,5 kN
C0 - Static load rating	11,2 kN
Operating temperature min.	-20 °C
Operating temperature max.	100 °C

OTHER FEATURES

Mass	1,13 kg
Recommended tightening torque for set screw	11.5 N-m