



The Timken Company


4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Bearing Unit - Adapter Sleeve UKF218 - H2318, UKF 200 Four-Bolt Flanged Mounted Bearings - Adapter Sleeve Locking




[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#)

Specifications

Bearing Unit - Adapter Sleeve	UK218 - H2318
Shaft Size d	80 mm
Adapter Sleeve Number¹	H2318
Locking Style	Adapter Sleeve Locking
Housing Construction	Four-Bolt Square Flange

Dimensions


Total Length L	235 mm 9.252 in
 Housing Width A	68 mm 2.677 in

Bolt Hole Spacing J	187 mm 7.362 in
Bolt Hole Size N	23 mm 0.906 in
Flange Thickness A1	25 mm 0.984 in
Center of Bearing from Housing End A2	40 mm 1.575 in
Center of Bearing from Bearing End Y	49.5 mm 1.949 in
Dimension B1	86 mm 3.386 in
Dimension A0	89.5 mm 3.531 in
Grease Nipple Size	A-R1/8

Basic Load Ratings

Static Load Rating	71500 N 16074 lbf
Dynamic Load Rating	96100 N 21604 lbf

¹ Purchase the Adapter Sleeve separately



Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.	FOR DISCUSSION ONLY
--	---------------------