



## Plummer block housing units RASE75-XL (Series RASE)

cast iron housing, radial insert ball bearing with eccentric locking collar, R seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	75 mm
L	265 mm
H <sub>2</sub>	164 mm
A	66 mm
A <sub>1</sub>	48 mm
B <sub>1</sub>	67 mm
d <sub>3 max</sub>	100 mm
H	82,5 mm
H <sub>1</sub>	27,5 mm
J	210 mm
N	22 mm

N <sub>1</sub>	30 mm	
Q	M6	
S <sub>1</sub>	45,5 mm	
m	6,58 kg	Mass
C <sub>r</sub>	66000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	44500 N	Basic static load rating, radial
	ASE15	Designation of housing
	GE75-XL-KRR-B	Designation of bearing



