



# ISO cylinder DSBF-C-100-25-PPVA-N3-R

Part number: 1782253

FESTO



[PDF](#) General operating condition

## Data sheet

| Feature                                                      | Value                                                                                      |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Stroke                                                       | 25 mm                                                                                      |
| Piston diameter                                              | 100 mm                                                                                     |
| Piston rod thread                                            | M20x1.5                                                                                    |
| Cushioning                                                   | Pneumatic cushioning, adjustable at both ends                                              |
| Mounting position                                            | optional                                                                                   |
| Conforms to standard                                         | ISO 15552                                                                                  |
| Piston-rod end                                               | Male thread                                                                                |
| Design                                                       | Piston<br>Piston rod<br>Profile barrel                                                     |
| Position detection                                           | Via proximity switch                                                                       |
| Symbol                                                       | 00991235                                                                                   |
| Operating pressure                                           | 0.04 MPa ... 1.2 MPa                                                                       |
| Operating pressure                                           | 0.4 bar ... 12 bar                                                                         |
| Mode of operation                                            | Double-acting                                                                              |
| Operating medium                                             | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium                           | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC                               | 3 - high corrosion stress                                                                  |
| LABS (PWIS) conformity                                       | VDMA24364-B2-L                                                                             |
| Ambient temperature                                          | -20 °C ... 80 °C                                                                           |
| Impact energy in end positions                               | 2.5 J                                                                                      |
| Cushioning length                                            | 31 mm                                                                                      |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke  | 4418 N                                                                                     |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 4712 N                                                                                     |
| Moving mass                                                  | 1143 g                                                                                     |
| Moving mass for 0 mm stroke                                  | 1045 g                                                                                     |
| Additional moving mass per 10 mm stroke                      | 39 g                                                                                       |
| Product weight                                               | 4816 g                                                                                     |
| Basic weight for 0 mm stroke                                 | 4551 g                                                                                     |
| Additional weight per 10 mm stroke                           | 106 g                                                                                      |
| Type of mounting                                             | Either:<br>Via female thread<br>With accessories                                           |
| Pneumatic connection                                         | G1/2                                                                                       |
| Note on materials                                            | RoHS-compliant                                                                             |

| Feature                    | Value                            |
|----------------------------|----------------------------------|
| Material cover             | Die-cast aluminium, coated       |
| Material piston seal       | TPE-U(PU)                        |
| Material piston            | Wrought aluminium alloy          |
| Material piston rod        | High-alloy stainless steel       |
| Material piston rod wiper  | TPE-U(PU)                        |
| Buffer seal material       | TPE-U(PU)                        |
| Cushioning piston material | POM                              |
| Material cylinder barrel   | Anodised wrought aluminium alloy |
| Material nut               | High-alloy stainless steel       |
| Material bearing           | POM                              |
| Material collar screws     | Galvanised steel                 |