



## Plummer block housing units RASEA25-XL-N (Series RASEA)

cast iron housing, radial insert ball bearing with adapter sleeve, R seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	25 mm
L	130 mm
H <sub>2</sub>	70 mm
A	36 mm
A <sub>1</sub>	21 mm
B <sub>1</sub>	28 mm
d <sub>3 max</sub>	38 mm
H	36,5 mm
H <sub>1</sub>	14,5 mm
J	102,5 mm
N	11 mm
N <sub>1</sub>	19 mm

Q	Rp1/8	
m	0,6 kg	Mass
Cr	14400 N	Basic dynamic load rating, radial
C0r	8100 N	Basic static load rating, radial
	ASE05	Designation of housing
	GSH25-XL-2RSR-B	Designation of bearing
	KASK05	Bearing end cap, closed design. To be ordered separately.
	Slot for bearing end cap	



