

## X-Tower 2.8m Scaffold Tower



## **Specifications**

Brand: TubescaWarranty: 3-yearMax Load: 150kgStandard: EN1004Material: Aluminium

- Commodity Code: 76169990 - Country of Origin: FR

- Recommended Usage: Intensive

#### **Common Dimensions**

- Platform Length: 1540mm - Platform Width: 600mm

- Distance Between Rungs: 250mm

## **Availability & Delivery**

Non-stock item. Delivery up to 28 days. (See exceptions, if applicable, overleaf)

[Representative image of product]

#### **Product Description**

The X-Tower can be erected in three minutes by one person with the minimum of training from the ground for maximum safety. The compact design can be stored and transported inside a small van and erected by one person in three minutes. Manufactured using industrial grade components for frequent use. Intuitive gravity latches make rung-by-rung height adjustment effortless allowing the tower to be quickly deployed to your desired height. Compact closed dimensions of 1.34m opens up to 3.1m x 2.0m platform.

#### **Features**

- Revolutionary Telescopic design can be erected in less than 3 minutes by one person
- Industrial strength design and components for frequent use
- Effortless multi-height adjustment up to a 2.8m platform height
- Two components only, tower frame and folding, anti-slip platform with integrated toe-boards
- Compacts down to fit inside a small trade van
- 4 x Locking heavy-duty castors
- Stabiliser supports are millimetre adjustable for precise levelling
- No loose components to forget or leave behind

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.



# X-Tower 2.8m Scaffold Tower

#### **Product Dimensions**

SKU	Platform Height <sup>2</sup> (mm)	Overall Height (mm)	Approx. Working Height <sup>1</sup> (mm)	Stabiliser Length x Width (mm)	Nett Weight (kg)
3010-036	2800	4400	4400	n/a x n/a	75.0

<sup>&</sup>lt;sup>1</sup> Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate.

#### **Shipping Dimensions**

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
3010-036	3178740162016	1410	920	980	1.271	75.0

### **Optional Extras / Spare Parts**

SKU	Description
3010-037	X-Tower Carriage Trolley

Packaging Material: Heavy-duty Cardboard Sleeve, Poly Wrap And Foam Inserts

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

<sup>&</sup>lt;sup>2</sup> Can be used as a free standing tower with a platform height of up to 8m (26ft) outdoors or 12m (39ft) indoors. To go beyond these limits the structure must be tied off according to the manufacturer's instructions.