

## **TECHNICAL DATASHEET**

## **Black Sidley S3 SRC SHOES**

Reference 885942 to 885953

Standard: EN ISO 20345 : 2011 S3 SRC A

UK CA

Sizes: 36 to 47



<u>Description:</u> Low derby type shoe, outdoor style, black colour.

Water-repellent full grain leather upper. Breathable mesh lining for better moisture transfer to the outside, high breathability and quick drying. Composite safety toe cap. Flexible "no metal" anti-perforation sole.

Dual density PU sole.

Protects the operator in the event of an electrical discharge by a minimum resistance of 0.75 M-Ohms between the ground and the human body, while protecting both sensitive material and explosive atmospheres by limiting the force of possible electrostatic overload of the human body within 35 M-Ohms whose spark-like discharge could ignite an explosion or destroy sensitive material.

## **Strong points:**

Light shoe.

Padded heel collar, ensures comfort and protection of the Achilles tendon.

Optimal depth crampons.

Anatomically formed footbed.

100% metal free.

Weight: 790g (weight of a foot in size 42)

Ceramic / water-detergent SRA Flat 0.52 / heel 0.53 Steel / Glycerin SRB Flat 0.19 / heel 0.18

## Anti-perforation protection

Non-metallic material for safety footwear made of multiple textile layers of extremely tearproof fibers. The midsole offers greater comfort, flexibility, cold insulation, humidity absorption and shock absorption to the wearer.