




Technical datasheet

NU2313EG1C3

Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

Visual(s)



Product definition

d	65 mm
D	140 mm
B	48 mm
E	124.5 mm
F	82.5 mm
rs min	2.1 mm
r1s min	2.1 mm
Radial clearance class	C3
Mass (without HJ ring)	3.46 kg
Brand	NTN

Product performance

Dynamic load, C	248 kN
Static load, C0	287 kN
Fatigue limit load, Cu	34.7 kN
Nlim (oil)	4,800 rpm
Nlim (grease)	4,100 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.73 Hz
Characteristic outer ring frequency, BPF0	5.18 Hz
Characteristic inner ring frequency, BPF1	7.82 Hz

Abutment dimensions

da min	76 mm
da max	81 mm
db min	85 mm
Da max	129 mm
ra max	2 mm
r1a max	2 mm

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$Po = Fr$$