

Carriages KWVE30-B-L (Series KWVE..-B-L)

long carriage, four-row, full complement ball set

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

H	42 mm	
B	90 mm	
L	127 mm	
1)	Locating face	
2)	Marking	
A ₁	31 mm	
A ₂	9 mm	
A ₃	11,5 mm	
A ₄	7 mm	
aL max	71 mm	aL and aR are dependent on the guideway length.
aL min	20 mm	aL and aR are dependent on the guideway length.
aR max	71 mm	aL and aR are dependent on the guideway length.
aR min	20 mm	aL and aR are dependent on the guideway length.

b	28 mm	Tolerance: -0,005/-0,03
d ₁	9 mm	
D ₂	8,6 mm	
G ₂	M10	for screws to DIN ISO 4762-12.9 Max. tightening torque [MA]: M5 = 5,8 Nm M6 = 10 Nm M8 = 24 Nm M10 = 41 Nm M12 = 83 Nm M14 = 140 Nm The stated torques represent maximum values for the reliable transmission of forces in vibration-free, quasistatic applications (S0=1). We recommend that the tightening torques of the screw connection to the adjacent construction should be determined at the customer under the specific application conditions and operating conditions, observing the data in VDI Guideline 2230 Part 1 (2015) and the data in the description.
G ₃	7 mm	Maximum permissible screw depth for lubrication connectors.
G ₄	7 mm	Maximum permissible screw depth for lubrication connectors.
h	23,5 mm	
H ₁	5,9 mm	
h ₁	11 mm	
H ₄	13,8 mm	
H ₅	6,25 mm	
J _B	72 mm	
J _L	52 mm	


jL	80 mm	
JL6	29,5 mm	
JLZ	44 mm	
K1	M8	for screws to DIN ISO 4762-12.9 Max. tightening torque [MA]: M4 = 5 Nm M5 = 10 Nm M6 = 17 Nm M8 = 24 Nm M10 = 83 Nm M12 = 140 Nm M14 = 220 Nm The stated torques represent maximum values for the reliable transmission of forces in vibration-free, quasistatic applications (S0=1). We recommend that the tightening torques of the screw connection to the adjacent construction should be determined at the customer under the specific application conditions and operating conditions, observing the data in VDI Guideline 2230 Part 1 (2015) and the data in the description.
K3	M8	for screws to DIN ISO 4762-12.9 Max. tightening torque [MA]: M4 = 5 Nm M5 = 10 Nm M6 = 17 Nm M8 = 24 Nm M10 = 83 Nm M12 = 140 Nm M14 = 220 Nm The stated torques represent maximum values for the reliable transmission of forces in vibration-free, quasistatic applications (S0=1). We recommend that the tightening torques of the screw connection to the adjacent construction should be determined at the customer under the specific application conditions and operating conditions, observing the data in VDI Guideline 2230 Part 1 (2015) and the data in the description.



K ₆	M8	for screws to DIN 7984-8.8 Max. tightening torque [MA]: M4 = 2 Nm M5 = 4 Nm M6 = 8 Nm M8 = 12 Nm The stated torques represent maximum values for the reliable transmission of forces in vibration-free, quasistatic applications (S0=1). We recommend that the tightening torques of the screw connection to the adjacent construction should be determined at the customer under the specific application conditions and operating conditions, observing the data in VDI Guideline 2230 Part 1 (2015) and the data in the description.
L ₁	100 mm	
l _{max}	5860 mm	Maximum length of single-piece guideways. Permissible guideway segments, see Technical principles
L _S	1,65 mm	
T ₅	12 mm	
T ₆	11,5 mm	
mw	1,7 kg	Mass of carriage
ms	4,3 kg/m	Mass of guideway
c	34500 N	Basic dynamic load rating
C ₀	74000 N	Basic static load rating
		Calculation of basic load rating according to ISO 14728-1. increased basic dynamic load rating possible on the basis of practical experience.

The full load rating can only be supported if the full thread length is used and the adjacent construction is correspondingly dimensioned.


M_{0x}	1310 Nm	Static moment rating about X axis
M_{0y}	1240 Nm	Static moment rating about Y axis
M_{0z}	1240 Nm	Static moment rating about Z axis

Lubrication connectors are included loose:
 S04 with KUV20-B
 S05 with KUV25-B to KUV55-B
 S16 with KUV15-B







Lubrication connector on lateral face



Lubrication connector on end face



Load directions



Lubrication connector

