

4-way pneumatic valves for pipe connection/sub-base mounting


4/2



Port size	Orifice (mm)	Flow factors (L/min)	Admissible differential pressure bar			Fluid temp. °C Gas	Seat disc	Reference numbers				Power consumption (W)		Wt. (g)	El. Part Group *	Dim ref.
			Min	Max				Global valve reference	Valve reference no.	Housing	Coil	DC	AC			

Anod. aluminium body/Pipe mounting

4/2 - Pilot operated -



1/4	6	630	1	10	10	75	NBR	7341BAG2JNMO	341B3403	1	2995	481865	9	8	700	2	36
	6	630	1	10	10	75	NBR				4270	481000	8	8	820	2	
	6	630	1	10	10	75	NBR	7341BAG2JNMR	341B34	2	2995	481865	9	8	700	2	36
	6	630	1	10	10	75	NBR				4270	481000	8	8	820	2	
	6	630	1	10	-	75	NBR	7341BAG2JNL8	341B3480	2	2995	482740	1.6	-	700	6	36
	6	560	1	10	-	75	NBR	-	341B3490	3	-	483580.01	4	0.4	-	665	7

Table continued on page 190

Notes:

* See Electrical Parts Group table at end of section

1. Without flow regulators

2. Flow regulating screws standard

3. Other coil-housing available: 488650.01, 488660.01, 488670.01 (refer to electrical parts at end of this section)

4. This reference no. is for the complete electrical part (coil + housing)