



## Fibre Sealing Washers



Engex sealing washers maintain the Ingress Protection (IP) rating between the equipment and cable gland. It may be necessary to fit an entry thread sealing washer at the gland entry interface. The need for a sealing washer will very much depend on the IP rating and code of protection of the equipment and the type of entry holes available within that equipment.

### Order Codes

code	description
<b>20FW</b>	<b>M20 Fibre Washer</b>
<b>25FW</b>	<b>M25 Fibre Washer</b>
<b>32FW</b>	<b>M32 Fibre Washer</b>
<b>40FW</b>	<b>M40 Fibre Washer</b>
<b>63FW</b>	<b>M63 Fibre Washer</b>

# IP68 Dome-Topped Plastic Glands



Nylon glands are made from a premium quality nylon IP68. Compression glands are supplied with IP rated washer and lock nut. Suitable for use with all types of un-armoured cables providing an environmental seal.

### Features & Benefits

Premium quality. IP68. UL approved nylon 66, 94V-2. Supplied with lock nut and IP seal. RU E186042, CE and RoHS compliant. 4 colours: grey, black, white and red/ Packed in 10s.

### Order Codes

code	description
<b>HAM16BK</b>	<b>16mm IP68 Black Nylon Gland</b>
<b>HAM16G</b>	<b>16mm IP68 Grey Nylon Gland</b>
<b>HAM16W</b>	<b>16mm IP68 White Nylon Gland</b>
<b>HAM20BK</b>	<b>20mm IP68 Black Nylon Gland</b>
<b>HAM20G</b>	<b>20mm IP68 Grey Nylon Gland</b>
<b>HAM20R</b>	<b>20mm IP68 Red Nylon Gland</b>
<b>HAM20W</b>	<b>20mm IP68 White Nylon Gland</b>
<b>HAM25BK</b>	<b>25mm IP68 Black Nylon Gland</b>
<b>HAM25G</b>	<b>25mm IP68 Grey Nylon Gland</b>
<b>HAM25W</b>	<b>25mm IP68 White Nylon Gland</b>
<b>HAM32BK</b>	<b>32mm IP68 Black Nylon Gland</b>
<b>HAM32G</b>	<b>32mm IP68 Grey Nylon Gland</b>
<b>HAM32W</b>	<b>32mm IP68 White Nylon Gland</b>
<b>HAM40BK</b>	<b>40mm IP68 Black Nylon Gland</b>
<b>HAM40G</b>	<b>40mm IP68 Grey Nylon Gland</b>
<b>HAM50BK</b>	<b>50mm IP68 Black Nylon Gland</b>
<b>HAM50G</b>	<b>50mm IP68 Grey Nylon Gland</b>

N.B: All products come with lock nut and IP washer.

## Technical Information



code	mounting hole D1	D2	B1	L1	L2	L3	cable range
<b>HAM16</b>	<b>16</b>	<b>10.8</b>	<b>9.6</b>	<b>15.7</b>	<b>14.4</b>	<b>16.7</b>	<b>5~10</b>
<b>HAM20</b>	<b>20</b>	<b>14.8</b>	<b>12.9</b>	<b>15.0</b>	<b>19.5</b>	<b>18.4</b>	<b>10~14</b>
<b>HAM25</b>	<b>25</b>	<b>18.6</b>	<b>16.4</b>	<b>15.0</b>	<b>18.7</b>	<b>22.3</b>	<b>13~18</b>
<b>HAM32</b>	<b>32</b>	<b>26.0</b>	<b>23.4</b>	<b>14.7</b>	<b>20.3</b>	<b>26.2</b>	<b>18~25</b>
<b>HAM40</b>	<b>40</b>	<b>33.0</b>	<b>30.6</b>	<b>17.7</b>	<b>23.4</b>	<b>31.6</b>	<b>22~32</b>
<b>HAM50</b>	<b>50</b>	<b>41.2</b>	<b>38.2</b>	<b>17.3</b>	<b>25.7</b>	<b>31.6</b>	<b>30~38</b>
<b>HAM63</b>	<b>63</b>	<b>54.1</b>	<b>44.0</b>	<b>18.5</b>	<b>27.0</b>	<b>32.6</b>	<b>34~44</b>