




Technical datasheet

NJ2211ET2XC3

Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, polyamide cage.

Visual(s)



Product definition

d	55 mm
D	100 mm
B	25 mm
E	90 mm
F	66 mm
d1	70.8 mm
rs min	1.5 mm
r1s min	1.1 mm
Radial clearance class	C3
Mass (without HJ ring)	0.77 kg
Brand	NTN

Product performance

Dynamic load, C	97 kN
Static load, C0	114 kN
Fatigue limit load, Cu	13.9 kN
Nlim (oil)	6,600 Tr/min
Nlim (grease)	5,600 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.35 Hz
Characteristic outer ring frequency, BPF0	6.77 Hz
Characteristic inner ring frequency, BPFI	9.23 Hz

Abutment dimensions

da min	63 mm
da max	65 mm
dc min	73 mm
Da max	92 mm
ra max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$Po = Fr$$