



5/2 Single and double solenoid actuated Glandless valves flow = 1.02 Cv (1000 l/min)

	Model	Function	Actuation	Pilot supply	Pilot pressure psi (bar)	Operating pressure psi (bar)	Manual override	Voltage
	VS26G511DF313A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Push only	24 VDC 1.2W
	VS26G511DF318A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Push only	115 VAC 1.5VA
	VS26G511DF213A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Push & turn	24 VDC 1.2W
	VS26G511DF218A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Push & turn	115 VAC 1.5VA
	VS26G511DF513A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Extended, push only	24 VDC 1.2W
	VS26G511DF518A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Extended, push only	115 VAC 1.5VA
	VS26G522DF313A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 232 (-0.9 to 16)	Push only	24 VDC 1.2W
	VS26G522DF318A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 232 (-0.9 to 16)	Push only	115 VAC 1.5VA
	VS26G522DF213A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 232 (-0.9 to 16)	Push & turn	24 VDC 1.2W
	VS26G522DF218A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 232 (-0.9 to 16)	Push & turn	115 VAC 1.5VA
	VS26G522DF513A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 232 (-0.9 to 16)	Extended, push only	24 VDC 1.2W
	VS26G522DF518A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 232 (-0.9 to 16)	Extended, push only	115 VAC 1.5VA
	VS26G517DF313A	5/2	Sol/Spring	Internal	-	23 to 145 (1.6 to 10)	Push only	24 VDC 1.2W
	VS26G517DF318A	5/2	Sol/Spring	Internal	-	23 to 145 (1.6 to 10)	Push only	115 VAC 1.5VA
	VS26G517DF213A	5/2	Sol/Spring	Internal	-	23 to 145 (1.6 to 10)	Push & turn	24 VDC 1.2W
	VS26G517DF218A	5/2	Sol/Spring	Internal	-	23 to 145 (1.6 to 10)	Push & turn	115 VAC 1.5VA
	VS26G517DF513A	5/2	Sol/Spring	Internal	-	23 to 145 (1.6 to 10)	Extended, push only	24 VDC 1.2W
	VS26G517DF518A	5/2	Sol/Spring	Internal	-	23 to 145 (1.6 to 10)	Extended, push only	115 VAC 1.5VA
	VS26G527DF313A	5/2	Sol/Spring	External	23 to 145 (1.6 to 10)	26" Hg to 232 (-0.9 to 16)	Push only	24 VDC 1.2W
	VS26G527DF318A	5/2	Sol/Spring	External	23 to 145 (1.6 to 10)	26" Hg to 232 (-0.9 to 16)	Push only	115 VAC 1.5VA
	VS26G527DF213A	5/2	Sol/Spring	External	23 to 145 (1.6 to 10)	26" Hg to 232 (-0.9 to 16)	Push & turn	24 VDC 1.2W
	VS26G527DF218A	5/2	Sol/Spring	External	23 to 145 (1.6 to 10)	26" Hg to 232 (-0.9 to 16)	Push & turn	115 VAC 1.5VA
	VS26G527DF513A	5/2	Sol/Spring	External	23 to 145 (1.6 to 10)	26" Hg to 232 (-0.9 to 16)	Extended, push only	24 VDC 1.2W
	VS26G527DF518A	5/2	Sol/Spring	External	23 to 145 (1.6 to 10)	26" Hg to 232 (-0.9 to 16)	Extended, push only	115 VAC 1.5VA

5/2 Single and double solenoid actuated Softseal valves flow = 1.37 Cv (1350 l/min)

	Model	Function	Actuation	Pilot supply	Pilot pressure psi (bar)	Operating pressure psi (bar)	Manual override	Voltage
	VS26S511DF313A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Push only	24 VDC 1.2W
	VS26S511DF318A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Push only	115 VAC 1.5VA
	VS26S511DF213A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Push & turn	24 VDC 1.2W
	VS26S511DF218A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Push & turn	115 VAC 1.5VA
	VS26S511DF513A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Extended, push only	24 VDC 1.2W
	VS26S511DF518A	5/2	Sol/Sol	Internal	-	29 to 145 (2 to 10)	Extended, push only	115 VAC 1.5VA
	VS26S522DF313A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Push only	24 VDC 1.2W
	VS26S522DF318A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Push only	115 VAC 1.5VA
	VS26S522DF213A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Push & turn	24 VDC 1.2W
	VS26S522DF218A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Push & turn	115 VAC 1.5VA
	VS26S522DF513A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Extended, push only	24 VDC 1.2W
	VS26S522DF518A	5/2	Sol/Sol	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Extended, push only	115 VAC 1.5VA
	VS26S517DF313A	5/2	Sol/Spring	Internal	-	29 to 145 (2 to 10)	Push only	24 VDC 1.2W
	VS26S517DF318A	5/2	Sol/Spring	Internal	-	29 to 145 (2 to 10)	Push only	115 VAC 1.5VA
	VS26S517DF213A	5/2	Sol/Spring	Internal	-	29 to 145 (2 to 10)	Push & turn	24 VDC 1.2W
	VS26S517DF218A	5/2	Sol/Spring	Internal	-	29 to 145 (2 to 10)	Push & turn	115 VAC 1.5VA
	VS26S517DF513A	5/2	Sol/Spring	Internal	-	29 to 145 (2 to 10)	Extended, push only	24 VDC 1.2W
	VS26S517DF518A	5/2	Sol/Spring	Internal	-	29 to 145 (2 to 10)	Extended, push only	115 VAC 1.5VA
	VS26S527DF313A	5/2	Sol/Spring	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Push only	24 VDC 1.2W
	VS26S527DF318A	5/2	Sol/Spring	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Push only	115 VAC 1.5VA
	VS26S527DF213A	5/2	Sol/Spring	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Push & turn	24 VDC 1.2W
	VS26S527DF218A	5/2	Sol/Spring	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Push & turn	115 VAC 1.5VA
	VS26S527DF513A	5/2	Sol/Spring	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Extended, push only	24 VDC 1.2W
	VS26S527DF518A	5/2	Sol/Spring	External	29 to 145 (2 to 10)	26" Hg to 145 (-0.9 to 10)	Extended, push only	115 VAC 1.5VA