

Remote type

Part number	Port size	Flow rate [l/min]	Output specification	Voltage
PF3W504-F03-1N	G3/8	0.5 to 4	(1 - 5V)	12 ~ 24 VDC
PF3W504-F03-2N			(4-20 mA)	
PF3W504-F03-1TN			2 (1 - 5V)	
PF3W520-F04-1N	G1/2	2 to 16	(1 - 5V)	
PF3W520-F04-2N			(4-20 mA)	
PF3W520-F04-1TN			2 (1 - 5V)	
PF3W540-F06-1N	G3/4	5 to 40	(1 - 5V)	
PF3W540-F06-2N			(4-20 mA)	
PF3W540-F06-1TN			2 (1 - 5V)	
PF3W511-F10-1N	G1	10 to 100	(1 - 5V)	
PF3W511-F10-2N			(4-20 mA)	
PF3W511-F10-1TN			2 (1 - 5V)	
PF3W521-F14-1N	G1 1/2	50 to 250	(1 - 5V)	
PF3W521-F14-2N			(4-20 mA)	
PF3W521-F14-1TN			2 (1 - 5V)	

- 1) Part numbers with "T" include temperature sensor.
 2) Lead wire with M8 connector is not included.
 3) NPN option available upon request.

Digital flow monitor for PVC piping:

Integrated type

Part number	Port size	Rated flow range [l/min]	Output specification	Voltage
PF3W711-U25-BN-M ●	25A (32 mm O.D.)	10 to 100	2 PNP	12 ~ 24 VDC
PF3W711-U25-EN-M			PNP + (1 - 5V)	
PF3W711-U25-FN-M			PNP + (4 - 20 mA)	
PF3W721-U30-BN-M	30A (38 mm O.D.)	30 to 250	2 PNP	
PF3W721-U30-EN-M			PNP + (1 - 5V)	
PF3W721-U30-FN-M			PNP + (4 - 20 mA)	

Remote type

Part number	Port size	Rated flow range [l/min]	Output specification	Voltage
PF3W511-U25-1N	25A (32 mm O.D.)	10 to 100	(1 - 5V)	12 ~ 24 VDC
PF3W511-U25-2N			(4 - 20 mA)	
PF3W521-U30-1N	30A (38 mm O.D.)	30 to 250	(1 - 5V)	
PF3W521-U30-2N			(4 - 20 mA)	

- 1) Lead wire with M8 connector is not included.

Digital flow monitor for PF3W series

Part number	Output specification	Voltage
PF3W30B-M	2 PNP	12 ~ 24 VDC
PF3W30E-M	PNP + (1 - 5V)	
PF3W30F-M	PNP + (4 - 20 mA)	

Accessories

Part number	Description
ZS-40-K	Bracket (with 4 tapping screws, 3 x 8, for PF3W704/720/504/520)
ZS-40-L	Bracket (with 4 tapping screws, 3 x 8, for PF3W740/540)
ZS-40-M	Bracket (with 4 tapping screws, 4 x 10, for PF3W711/511)
ZS-40-A	Lead wire (3 m) with M8 connector