

SAFETY SHOES CABULCO 2 Evol S3 HRO SRC

Item #	EAN	Product
847915	3660338089152	Size 3
847916	3660338089169	Size 4
847917	3660338089176	Size 5
847918	3660338089183	Size 6
847920	3660338089206	Size 7
847921	3660338089213	Size 8
847922	3660338089220	Size 9
847923	3660338089237	Size 10
847925	3660338089251	Size 11
847926	3660338089268	Size 12
847927	3660338089275	Size 13

Description

Standard : EN ISO 20345 : 2011 S3 HRO SRC A

UK
CA

Upper in pull-up water resistant leather. On protection tip of abrasion-resistant, heel support of TPU with heel tabs. Reflecting lateral inserts.

Lining of breathable Mesh material. Quilted upper top, quilted, lined tab. Rubber/PU sole. Removable insole with EVA insert for a better shock absorbent heel.



Characteristics Very good resistance to contact heat (300°C). Self-cleaning sole and deep structure crampons. Safety toe cap of synthetic material, and perforation-resistant non-metallic insole compliant with standard 12568:2010. High-performance walking sole for the most aggressive environments. High resistance to abrasion.

Weight : 710 g in size 42

SLIP RESISTANCE SRC :

Test floor Ceramics lubricant water+detergent SRA

0.37 Flat

0.34 Heel contact angle 7°

Test floor Steel Lubricant Glycerin SRB

0.19 Flat

0.15 Heel contact angle 7°

SLIP RESISTANCE REQUIREMENTS ACCORDING TO THE EN ISO 20345:2011 METHOD REQUESTED BY EN 13287:2012

Applications

Processing industries, used oils, machining swarf, hydrocarbons, hot environments.