



Bubblemat

Smart anti-fatigue mat with a distinctive bubbled surface



- Raised bubble patterned surface stimulates feet and legs to aid circulation.
- Underfoot cushioning also makes prolonged occupational standing more comfortable.
- A choice of materials depending on the demands of the environment (dry use only).
- Complete mats suitable for workstations and interlocking sections available for longer production lines.

Parts

| Part Number | Size | Colour | Weight |
|-------------|---|-----------------|----------|
| BF010001 | 0.6 m x 0.9 m (edged all round) | Black | 6.35 kg |
| BF010002 | 0.9 m x 1.2 m (edged all round) | Black | 10.50 kg |
| BF010003 | 0.6 m x 0.9 m (interlocking end piece) | Black | 6.35 kg |
| BF010004 | 0.6 m x 0.9 m (interlocking middle piece) | Black | 6.35 kg |
| BF010001N | 0.6 m x 0.9 m (edged all round) | Black (Nitrile) | 5.00 kg |
| BF010002N | 0.9 m x 1.2 m (edged all round) | Black (Nitrile) | 11.00 kg |
| BF010003N | 0.6 m x 0.9 m (interlocking end piece) | Black (Nitrile) | 5.00 kg |
| BF010004N | 0.6 m x 0.9 m (interlocking middle piece) | Black (Nitrile) | 5.00 kg |
| BF010701 | 0.6 m x 0.9 m (edged all round) | Safety | 5.00 kg |
| BF010702 | 0.9 m x 1.2 m (edged all round) | Safety | 11.00 kg |

Technical Specification

| | |
|--------------------------|---|
| Material | Standard - Natural rubber. Nitrile version - NBR. |
| Surface Finish | Bubble |
| Product Height | 14 mm |
| Product Weight | 10kg |
| Operating Temperature | -20°C to +50°C |
| Resistance to Chemicals | Not resistant to fat and mineral oil |
| Environmental Resistance | Suitable for predominantly dry environments |
| UV Resistance | Yes |
| Typical Applications | General industrial |
| Installation Method | Loose lay interlocking mats |
| Cleaning Method | Use a high pressure hose (not exceeding 60psi) to remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats |

Parts

| | | | |
|----------|---|--------|----------|
| BF010703 | 0.6 m x 0.9 m (interlocking end piece) | Safety | 5.00 kg |
| BF010704 | 0.6 m x 0.9 m (interlocking middle piece) | Safety | 11.00 kg |
| BF010705 | 0.9 m x 1.2 m (interlocking end piece) | Safety | 11.00 kg |
| BF010706 | 0.9 m x 1.2 m (interlocking middle piece) | Safety | 11.00 kg |

Technical Specification

| | |
|-------------------------|------------------------------------|
| Country of Origin | Sri Lanka |
| Storage and application | Mat should be covered by polythene |
| Tensile Strength | 3 MPa |
| Elongation | 250% |
| Application Temperature | -30 °C to 50 °C |
| Manufacturing process | Compression moulding |

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)116 240 1088 or email sales@cobaeurope.com