

# TECHNICAL DATASHEET

Update: 19/04/2021

#### **UNIVERSAL PRIMER**

| ltem # | EAN           | Product          |
|--------|---------------|------------------|
| 865210 | 3660338195860 | Universal primer |

## **Description**

A quick-drying primer (undercoat) to be applied to a surface to be covered with synthetic or acrylic paint. For interior and exterior use. Excellent adhesion to various surfaces, glass, ceramics, enamel, eternite, many plastics, cardboard, wood and metal.

#### **Characteristics**

Gross volume: 520 mLNet volume: 400 mL

## **Precautions for use**

Danger. Extremely flammable aerosol. Pressurized container: may burst under heat. Causes severe eye irritation. May cause drowsiness or dizziness. Harmful to aquatic organisms, causes long-term adverse effects. Repeated exposure may cause skin dryness or cracking.

#### **Instructions**

Cover the areas that are not to be painted! Shake the can for approx. 3 minutes. Perform a spray test. Apply several thin coats to level out small cavities and porous sealant surfaces. Spray distance approx. 25 cm. After drying (approx. 2-4 hours), sand with water (600 grain), clean and paint.

# Packaging and storage

- Unit
- Carton of 6 units
- Pallet of 1080 units

Store in a dry place. Protect from sunlight and heat sources. Do not expose to temperatures above 50°C.

