



# Spindle axis ELGA-BS-KF-120-500-0H-10P-ML

Part number: 8041840

FESTO



 General operating condition

## Data sheet

| Feature                                                           | Value                                            |
|-------------------------------------------------------------------|--------------------------------------------------|
| Working stroke                                                    | 500 mm                                           |
| Size                                                              | 120                                              |
| Stroke reserve                                                    | 0 mm                                             |
| Spindle diameter                                                  | 25 mm                                            |
| Spindle pitch                                                     | 10 mm/U                                          |
| Mounting position                                                 | optional                                         |
| Guide                                                             | Recirculating ball bearing guide                 |
| Design                                                            | Electromechanical linear axis<br>With ball screw |
| Type of motor                                                     | Stepper motor<br>Servo motor                     |
| Spindle type                                                      | Ball screw                                       |
| Symbol                                                            | 00991211                                         |
| Functional principle of measuring system                          | Incremental                                      |
| Max. acceleration                                                 | 15 m/s <sup>2</sup>                              |
| Max. rotational speed                                             | 3600 rpm                                         |
| Max. speed                                                        | 0.6 m/s                                          |
| Repetition accuracy                                               | ±0.02 mm                                         |
| LABS (PWIS) conformity                                            | VDMA24364 zone III                               |
| Degree of protection                                              | IP40                                             |
| Ambient temperature                                               | -10 °C ... 60 °C                                 |
| 2nd moment of area Iy                                             | 1240000 mm <sup>4</sup>                          |
| 2nd moment of area Iz                                             | 3800000 mm <sup>4</sup>                          |
| Idle torque at vmax                                               | 1.33 Nm                                          |
| Idle torque at vmin                                               | 1 Nm                                             |
| Max. force Fy                                                     | 5500 N                                           |
| Max. force Fz                                                     | 6890 N                                           |
| Fy at theoretical life value of 100 km (only guide consideration) | 20240 N                                          |
| Fz at theoretical life value of 100 km (only guide consideration) | 25355 N                                          |
| Max. moment Mx                                                    | 104 Nm                                           |
| Max. moment My                                                    | 680 Nm                                           |
| Max. moment Mz                                                    | 680 Nm                                           |
| Mx at theoretical life value of 100 km (only guide consideration) | 383 Nm                                           |
| My at theoretical life value of 100 km (only guide consideration) | 2502 Nm                                          |
| Mz at theoretical life value of 100 km (only guide consideration) | 2502 Nm                                          |
| Max. radial force at drive shaft                                  | 500 N                                            |

| Feature                                          | Value                                 |
|--------------------------------------------------|---------------------------------------|
| Max. feed force Fx                               | 3400 N                                |
| Torsional mass moment of inertia It              | 247000 mm <sup>4</sup>                |
| Mass moment of inertia JH per metre of stroke    | 2.756 kgcm <sup>2</sup>               |
| Mass moment of inertia JL per kg of working load | 0.0253 kgcm <sup>2</sup>              |
| Mass moment of inertia JO                        | 1.038 kgcm <sup>2</sup>               |
| Feed constant                                    | 10 mm/U                               |
| Moving mass                                      | 4459 g                                |
| Weight of additional slide                       | 3600 g                                |
| Additional weight per 10 mm stroke               | 101 g                                 |
| Dynamic deflection (moving load)                 | 0.05% of the axis length, max. 0.5 mm |
| Static deflection (load in standstill)           | 0.1% of the axis length               |
| Material end cap                                 | Wrought aluminium alloy<br>Anodised   |
| Material profile                                 | Wrought aluminium alloy<br>Anodised   |
| Note on materials                                | RoHS-compliant                        |
| Material drive cover                             | Wrought aluminium alloy<br>Anodised   |
| Material guide slide                             | Steel                                 |
| Material guide rail                              | Steel                                 |
| Material slide                                   | Wrought aluminium alloy<br>Anodised   |
| Material spindle nut                             | Steel                                 |
| Material spindle                                 | Steel                                 |