



A

"V" Series Basic Modules Size 1 (Without Pneumatic Connectors)



Single Solenoid



Double Solenoid

Size 1 Electro-Pneumatic Island Valve Modules, 24VDC

4-Way / 2-Position / Single Valve

	Solenoid	Weight	Part Number
	Single Solenoid (Monostable)	3.32 oz	P2M1V4ES2CV
	Double Solenoid (Bistable)	3.63 oz	P2M1V4EE2CV

4-Way / 2-Position / Dual Valve

	Solenoid	Weight	Part Number
	Solenoid Spring with Exhaust Check	3.63 oz	P2M1VJEE2CV

3-Way / 2-Position / Dual Valve

	Solenoid	Weight	Part Number
	Double Solenoid NC + NC with Exhaust Check	3.74 oz	P2M1VDEE2CV
	Double Solenoid NO + NO with Exhaust Check	3.74 oz	P2M1VCEE2CV
	Double Solenoid NC + NO with Exhaust Check	3.74 oz	P2M1VEEE2CV
	Single Solenoid NC with Exhaust Check	3.60 oz	P2M1V3ES2CV
	Center Exhaust = dual 3/2 NC + NC without Exhaust Check	3.74 oz	P2M1VGEE2CV

Pneumatic Connectors for Size 1 Modules



PMDYY1



HMDXX1



MMDVA2



FMD04-1



CMD04-1



FMD07-1B



CMD07-1B

		Elbow Version		Straight Version	
		Weight (oz)	Order Code	Weight (oz)	Order Code
Tube Push-in Connector	5/32" = 4mm OD	0.18	CMD04-1	0.07	FMD04-1
	6mm OD	0.18	CMD06-1	0.11	FMD06-1
	1/4" OD	0.18	CMD07-1B	0.11	FMD07-1B
Muffler for Exhaust Port	—	—	—	0.11	MMDVA2
Plug	—	—	—	0.18	PMDYY1
Double Male Union (For Peripheral Valve Modules)	—	—	—	0.21	HMDXX1

Note: 85 Durometer minimum for pneumatic connectors.

Note: Bold Options Standard