

TECHNICAL DATASHEET

Update : 25/02/2019

5 VARI FLUTE CARBIDE END MILL - STANDARD SERIES - STRAIGHT SHANK - SPECIAL



S



Characteristics

Ref.	EAN	Diameter mm	Type of tail	Tail diameter mm	Number of teeth	Length of cut mm	Total length mm	Angle of helix °	Centre cut	Coating	Radius mm
832315	3660338052118	4	Cylindrical HA	6	5	11	57	35/38	No	OZMX	0,1
832316	3660338052125	6	Cylindrical HA	6	5	13	57	35/38	No	OZMX	0,1
832317	3660338052132	8	Cylindrical HA	8	5	21	63	35/38	No	OZMX	0,2
832318	3660338052149	10	Cylindrical HA	10	5	22	72	35/38	No	OZMX	0,2
832319	3660338052156	12	Cylindrical HA	12	5	26	83	35/38	No	OZMX	0,2
832320	3660338052163	14	Cylindrical HA	14	5	26	92	35/38	No	OZMX	0,2
832321	3660338052170	16	Cylindrical HA	16	5	36	92	35/38	No	OZMX	0,3
832322	3660338052187	18	Cylindrical HA	18	5	36	92	35/38	No	OZMX	0,3
832323	3660338052194	20	Cylindrical HA	20	5	41	104	35/38	No	OZMX	0,3
843486	3660338067372	5	Cylindrical HA	6	5	13	57	35/38	Yes	OZMX	0,1