

**Connection block**  
**CPE14-3/2-PRS-3/8-2-NPT**  
Part number: 550610

**FESTO**



**Data sheet**

| Feature                                   | Value                         |
|-------------------------------------------|-------------------------------|
| Width dimension                           | 20 mm                         |
| Type code                                 | CPE14-PRS                     |
| Mounting position                         | Any                           |
| Max. no. of valve positions               | 2                             |
| Max. no. of pressure zones                | 2                             |
| Operating pressure                        | -0.896 bar ... 9.997 bar      |
| Corrosion resistance class (CRC)          | 2 - Moderate corrosion stress |
| Temperature of medium                     | -5 °C ... 50 °C               |
| Ambient temperature                       | -5 °C ... 50 °C               |
| Max. tightening torque for valve mounting | 1.22 Nm                       |
| Product weight                            | 174.636 g                     |
| Manifold block type of mounting           | With through-hole             |
| Pneumatic valve mounting type             | With internal thread          |
| Pneumatic connection 1                    | 3/8 NPT                       |
| Pneumatic connection 3                    | 3/8 NPT                       |
| Pneumatic connection 5                    | 3/8 NPT                       |
| Note on materials                         | RoHS-compliant                |
| Manifold rail material                    | Wrought aluminum alloy        |